

	R	eport on entire Annex		Annex Te	5, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference	INTERNATIONAL STANDARDS AND RECOMMENDED PRACTICES	Civil Aviation Rules (CAR) Part 1.	No Difference		Civil Aviation Rules, the Civil Aviation Act 1990, and Advisory Circulars are available on the CAANZ web site,
Definition	CHAPTER 1. GENERAL				http://www.caa.govt.nz. AIPNZ is available on http://:www.aip.net.nz.
	Note 1.— The object of the aeronautical information service (AIS) is to ensure the flow of aeronautical data and aeronautical information necessary for global air traffic management (ATM) system safety, regularity, economy and efficiency in an environmentally sustainable manner. The role and importance of aeronautical data and aeronautical information changed significantly with the implementation of area navigation (RNAV), performance-based navigation (PBN), airborne computer-based navigation systems, p e r f o r m a n c e - b a s e d c o m m u n i c a t i o n (PBC), performance-based surveillance (PBS), data link systems and satellite voice communications (SATVOICE). Corrupt, erroneous, late or missing aeronautical data and aeronautical information can potentially affect the safety of air navigation. Note 2.— These Standards and Recommended Practices				
	Note 2.— These Standards and Recommended Practices are to be used in conjunction with the Procedures for Air Navigation Services — ICAO Abbreviations and Codes (PANS-ABC, Doc 8400). Note 3.— These Standards and Recommended Practices are to be used in conjunction with the Procedures for Air Navigation Services — Aeronautical Information Management (PANS-AIM, Doc 10066).				



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
	Note 4.— Guidance material on the organization and operation of the AIS is contained in the Aeronautical Information Services Manual (Doc 8126).					
	1.1 Definitions					
	When the following terms are used in the Standards and Recommended Practices for the AIS, they have the following meanings:					
	<i>Aerodrome.</i> A defined area on land or water (including any buildings, installations and equipment) intended to be used either wholly or in part for the arrival, departure and surface movement of aircraft.					
Chapter 1 Reference	<i>Aerodrome mapping data (AMD).</i> Data collected for the purpose of compiling aerodrome mapping information. <i>Note.— Aerodrome mapping data is collected for purposes that include the improvement of the user's</i>	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.		
Definition	situational awareness, surface navigation operations, training, charting and planning.					
Chapter 1	Aerodrome mapping database (AMDB). A collection of	CARs.	Less protective	Not specifically defined.		
Reference	aerodrome mapping data organized and arranged as a structured data set.		or partially implemented or not implemented			
Definition						



New Zealand Annex 15, Amendme Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	<i>Aeronautical chart.</i> A representation of a portion of the Earth, its culture and relief, specifically designated to meet the requirements of air navigation.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.	See AIPNZ GEN 3.2 for range and availability.	
Chapter 1 Reference	<i>Aeronautical data.</i> A representation of aeronautical facts, concepts or instructions in a formalized manner suitable for communication, interpretation or processing.	CAR Part 1.	No Difference			
Definition						
Chapter 1 Reference Definition	<i>Aeronautical fixed service (AFS).</i> A telecommunication service between specified fixed points provided primarily for the safety of air navigation and for the regular, efficient and economical operation of air services.	CAR Part 1.	No Difference		Note: Subclause of Part 1 definition of aeronautical telecommunication service, which is aligned with Annex 10 Vol II definition.	
Chapter 1 Reference	<i>Aeronautical information.</i> Information resulting from the assembly, analysis and formatting of aeronautical data.	CAR Part 1.	No Difference			
Definition						
Chapter 1 Reference Definition	<i>Aeronautical Information Circular (AIC).</i> A notice containing information that does not qualify for the origination of a NOTAM or for inclusion in the AIP, but which relates to flight safety, air navigation, technical, administrative or legislative matters.	CAR Part 1.	No Difference			

Sixteenth edition 2018



	Annex 15, Amendment 43 Annex 15, Amendment 43					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	<i>Aeronautical information management (AIM).</i> The dynamic, integrated management of aeronautical information through the provision and exchange of quality-assured digital aeronautical data in collaboration with all parties.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.		
Chapter 1 Reference Definition	 Aeronautical information product. Aeronautical data and aeronautical information provided either as digital data sets or as a standardized presentation in paper or electronic media. Aeronautical information products include: Aeronautical Information Publication (AIP), including Amendments and Supplements; Aeronautical Information Circulars (AIC); aeronautical charts; NOTAM; and digital data sets. Note.—Aeronautical information products are intended primarily to satisfy international requirements for the exchange of aeronautical information. 	CAR Part 175.	Less protective or partially implemented or not implemented	Not specifically defined.	See AIPNZ GEN 3.1 and 3.2 for range and availability.	
Chapter 1 Reference Definition	<i>Aeronautical Information Publication (AIP).</i> A publication issued by or with the authority of a State and containing aeronautical information of a lasting character essential to air navigation.	CAR Part 1.	No Difference			



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	<i>Aeronautical information service (AIS).</i> A service established within the defined area of coverage responsible for the provision of aeronautical data and aeronautical information necessary for the safety, regularity and efficiency of air navigation.	CAR Part 1.	No Difference			
Chapter 1 Reference	<i>AIP Amendment.</i> Permanent changes to the information contained in the AIP.	CAR Part 1.	No Difference			
Definition						
Chapter 1 Reference	<i>AIP Supplement.</i> Temporary changes to the information contained in the AIP which are provided by means of special pages.	CAR Part 1.	No Difference			
Definition						
Chapter 1 Reference	<i>AIRAC.</i> An acronym (aeronautical information regulation and control) signifying a system aimed at advance notification, based on common effective dates, of circumstances that necessitate significant changes in operating practices.	CAR Part 1.	No Difference			
Definition						
Chapter 1 Reference Definition	<i>Air defence identification zone (ADIZ).</i> Special designated airspace of defined dimensions within which aircraft are required to comply with special identification and/or reporting procedures additional to those related to the provision of air traffic services.		Not Applicable		Not used in New Zealand.	

Sixteenth edition 2018 Annex 15, Amendment 43



Report on entire Annex

	Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	<i>Air traffic management (ATM).</i> The dynamic, integrated management of air traffic and airspace (including air traffic services, airspace management and air traffic flow management) — safely, economically and efficiently — through the provision of facilities and seamless services in collaboration with all parties and involving airborne and ground-based functions.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference Definition	 Application. Manipulation and processing of data in support of user requirements (ISO 19104*). * All ISO Standards referred to in this chapter are listed at 	(British Standard) BS ISO 19104:2016.	No Difference		Note: in this case where an equivalent Australian/New Zealand Standard has not been issued, Standards New Zealand publishes the British Standard.
Chapter 1 Reference Definition	the end of the chapter. Area navigation (RNAV). A method of navigation which permits aircraft operation on any desired flight path within the coverage of ground- or space-based navigation aids or within the limits of the capability of self-contained aids, or a combination of these. Note.— Area navigation includes performance-based navigation as well as other operations that do not meet the definition of performance-based navigation.	CAR Part 1.	No Difference		
Chapter 1 Reference Definition	ASHTAM. A special series NOTAM notifying by means of a specific format change in activity of a volcano, a volcanic eruption and/or volcanic ash cloud that is of significance to aircraft operations.		Not Applicable		Not used in New Zealand.

Sixteenth edition 2018



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	Assemble. A process of merging data from multiple sources into a database and establishing a baseline for subsequent processing. Note.— The assemble phase includes checking the data and ensuring that detected errors and omissions are rectified.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference Definition	<i>ATS surveillance service.</i> Term used to indicate a service provided directly by means of an ATS surveillance system.	AIPNZ GEN 2.2.	No Difference			
Chapter 1 Reference Definition	ATS surveillance system. A generic term meaning variously, ADS-B, PSR, SSR or any comparable ground-based system that enables the identification of aircraft. Note.— A comparable ground-based system is one that has been demonstrated, by comparative assessment or other methodology, to have a level of safety and performance equal to or better than monopulse SSR.	AIPNZ GEN 2.2.	No Difference			
Chapter 1 Reference Definition	<i>Automatic dependent surveillance</i> — <i>broadcast (ADS-B).</i> A means by which aircraft, aerodrome vehicles and other objects can automatically transmit and/or receive data such as identification, position and additional data, as appropriate, in a broadcast mode via a data link.	AIPNZ GEN 2.2.	No Difference			



	Report on entire Annex Annex 15, Amendment 43					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	 Automatic dependent surveillance — contract (ADS-C). A means by which the terms of an ADS-C agreement will be exchanged between the ground system and the aircraft, via a data link, specifying under what conditions ADS-C reports would be initiated, and what data would be contained in the reports. Note.— The abbreviated term "ADS contract" is commonly used to refer to ADS event contract, ADS demand contract, ADS periodic contract or an emergency mode. 	AIPNZ GEN 2.2	No Difference			
Chapter 1 Reference Definition	Automatic terminal information service (ATIS).Theautomatic provision of current, routine information to arriving and departing aircraft throughout 24 hours or a specified portion thereof:Data link-automatic terminal information service (D-ATIS). The provision of ATIS via data link.Voice-automatic terminal information service (Voice-ATIS).The provision of ATIS by means of continuous and repetitive voice broadcasts.	AIPNZ GEN 2.2, 2.2.1.	No Difference			
Chapter 1 Reference Definition	<i>Bare Earth.</i> Surface of the Earth including bodies of water and permanent ice and snow, and excluding vegetation and man-made objects.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		



	R	eport on entire Annex		Annex 15, Amendment 43		
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	<i>Calendar.</i> Discrete temporal reference system that provides the basis for defining temporal position to a resolution of one day (ISO 19108*).	(Australian Standard/New Zealand Standard) AS/NZS ISO 19108:2003.	No Difference			
Chapter 1 Reference Definition	<i>Canopy.</i> Bare Earth supplemented by vegetation height.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference Definition	Confidence level. The probability that the true value of a parameter is within a certain interval around the estimate of its value. Note.— The interval is usually referred to as the accuracy of the estimate.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.		
Chapter 1 Reference Definition	<i>Controller-pilot data link communications (CPDLC).</i> A means of communication between controller and pilot, using data link for ATC communications.	AIPNZ GEN 2.2.	No Difference			
Chapter 1 Reference Definition	<i>Culture.</i> All man-made features constructed on the surface of the Earth, such as cities, railways and canals.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		



New Zealand Annex 15, Anne					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	<i>Cyclic redundancy check (CRC).</i> A mathematical algorithm applied to the digital expression of data that provides a level of assurance against loss or alteration of data.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	Beyond scope of rules.
Chapter 1 Reference Definition	Danger area. An airspace of defined dimensions within which activities dangerous to the flight of aircraft may exist at specified times.	CAR 71.161.	No Difference		
Chapter 1 Reference Definition	<i>Data accuracy.</i> A degree of conformance between the estimated or measured value and the true value.	CARs.	Less protective or partially implemented or not implemented	Not defined in CARs.	
Chapter 1 Reference Definition	Data completeness. The degree of confidence that all of the data needed to support the intended use is provided.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	
Chapter 1 Reference Definition	<i>Data format.</i> A structure of data elements, records and files arranged to meet standards, specifications or data quality requirements.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	<i>Data integrity (assurance level).</i> A degree of assurance that an aeronautical data and its value has not been lost or altered since the origination or authorized amendment.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference Definition	<i>Data product.</i> Data set or data set series that conforms to a data product specification (ISO 19131*).	AS/NZS ISO 19131:2008.	No Difference			
Chapter 1 Reference Definition	 Data product specification. Detailed description of a data set or data set series together with additional information that will enable it to be created, supplied to and used by another party (ISO 19131*). Note.— A data product specification provides a description of the universe of discourse and a specification for mapping the universe of discourse to a data set. It may be used for production, sales, end-use or other purpose. 	AS/NZS ISO 19131:2008.	No Difference			
Chapter 1 Reference Definition	Data quality. A degree or level of confidence that the data provided meet the requirements of the data user in terms of accuracy, resolution, integrity (or equivalent assurance level), traceability, timeliness, completeness and format.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		



	Annex 15, Amer Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	<i>Data resolution.</i> A number of units or digits to which a measured or calculated value is expressed and used.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference	<i>Data set.</i> Identifiable collection of data (ISO 19101*).	AS/NZS ISO 19101.1:2015.	No Difference			
Definition						
Chapter 1 Reference	<i>Data set series.</i> Collection of data sets sharing the same product specification (ISO 19115*).	AS/NZS ISO 19115.1:2015.	No Difference			
Definition						
Chapter 1 Reference	<i>Data timeliness.</i> The degree of confidence that the data is applicable to the period of its intended use.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Definition						
Chapter 1 Reference Definition	Data traceability. The degree that a system or a data product can provide a record of the changes made to that product and thereby enable an audit trail to be followed from the end-user to the originator.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		



New Zealand Annex 15, Amer Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference	Datum. Any quantity or set of quantities that may serve as a reference or basis for the calculation of other quantities (ISO 19104*).	BS ISO 19104:2016.	No Difference		
Definition					
Chapter 1 Reference Definition	Digital Elevation Model (DEM). The representation of terrain surface by continuous elevation values at all intersections of a defined grid, referenced to common datum. Note.— Digital Terrain Model (DTM) is sometimes referred to as DEM.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	
Chapter 1 Reference Definition	<i>Direct transit arrangements.</i> Special arrangements approved by the public authorities concerned by which traffic which is pausing briefly in its passage through the Contracting State may remain under their direct control.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	
Chapter 1 Reference Definition	<i>Ellipsoid height (geodetic height).</i> The height related to the reference ellipsoid, measured along the ellipsoidal outer normal through the point in question.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	



New Zealand Annex 15, Amen Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	<i>Feature.</i> Abstraction of real world phenomena (ISO 19101*).	AS/NZS ISO 19101.1:2015.	No Difference		
Chapter 1 Reference Definition	<i>Feature attribute.</i> Characteristic of a feature (ISO 19101*). Note.— A feature attribute has a name, a data type and a value domain associated with it.	AS/NZS ISO 19101.1:2015.	No Difference		
Chapter 1 Reference Definition	 Feature operation. Operation that every instance of a feature type may perform (ISO 19110*). Note.— An operation upon the feature type dam is to raise the dam. The result of this operation is to raise the level of water in the reservoir. 	AS/NZS ISO 19110:2006.	No Difference		
Chapter 1 Reference Definition	<i>Feature relationship.</i> Relationship that links instances of one feature type with instances of the same or a different feature type (ISO 19101*).	AS/NZS ISO 19101.1:2015.	No Difference		
Chapter 1 Reference Definition	<i>Feature type.</i> Class of real world phenomena with common properties (ISO 19110*). Note.— In a feature catalogue, the basic level of classification is the feature type.	AS/NZS ISO 19110:2006.	No Difference		



New Zealand	Annex 15, Amendment 43						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 1 Reference Definition	<i>Geodesic distance.</i> The shortest distance between any two points on a mathematically defined ellipsoidal surface.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.			
Chapter 1 Reference Definition	<i>Geodetic datum.</i> A minimum set of parameters required to define location and orientation of the local reference system with respect to the global reference system/frame.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	Common usage term.		
Chapter 1 Reference Definition	Geoid. The equipotential surface in the gravity field of the Earth which coincides with the undisturbed mean sea level (MSL) extended continuously through the continents. Note.— The geoid is irregular in shape because of local gravitational disturbances (wind tides, salinity, current, etc.) and the direction of gravity is perpendicular to the geoid at every point.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.			
Chapter 1 Reference Definition	 Geoid undulation. The distance of the geoid above (positive) or below (negative) the mathematical reference ellipsoid. Note.— In respect to the World Geodetic System — 1984 (WGS-84) defined ellipsoid, the difference between the WGS-84 ellipsoidal height and orthometric height represents WGS-84 geoid undulation. 	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.			



New Zealand	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	 Gregorian calendar. Calendar in general use; first introduced in 1582 to define a year that more closely approximates the tropical year than the Julian calendar (ISO 19108*). Note.— In the Gregorian calendar, common years have 365 days and leap years 366 days divided into twelve sequential months. 	AS/NZS ISO 19108:2003.	No Difference			
Chapter 1 Reference Definition	<i>Height.</i> The vertical distance of a level, point or an object considered as a point, measured from a specific datum.	CAR Part 1.	No Difference			
Chapter 1 Reference Definition	<i>Heliport.</i> An aerodrome or a defined area on a structure intended to be used wholly or in part for the arrival, departure and surface movement of helicopters.	CAR Part 1.	No Difference			
Chapter 1 Reference Definition	<i>Human factors principles.</i> Principles which apply to aeronautical design, certification, training, operations and maintenance and which seek safe interface between the human and other system components by proper consideration to human performance.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	Common usage term.	

Sixteenth edition 2018



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	 Integrity classification (aeronautical data). Classification based upon the potential risk resulting from the use of corrupted data. Aeronautical data is classified as: a) routine data: there is a very low probability when using corrupted routine data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe; b) essential data: there is a low probability when using corrupted essential data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe; c) critical data: there is a high probability when using corrupted critical data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe; and c) critical data: there is a high probability when using corrupted critical data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe; and 	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.		
Chapter 1 Reference Definition	<i>International airport.</i> Any airport designated by the Contracting State in whose territory it is situated as an airport of entry and departure for international air traffic, where the formalities incident to customs, immigration, public health, animal and plant quarantine and similar procedures are carried out.	CAR Part 1.	No Difference			
Chapter 1 Reference Definition	<i>International NOTAM office (NOF).</i> An office designated by a State for the exchange of NOTAM internationally.	CAR Part 1.	No Difference			



Report on entire Annex 15, Ame					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	<i>Logon address.</i> A specified code used for data link logon to an ATS unit.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	
Chapter 1 Reference	<i>Manoeuvring area.</i> That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, excluding aprons.	CAR Part 1.	No Difference		
Definition					
Chapter 1 Reference	<i>Metadata.</i> Data about data (ISO 19115*). Note.— A structured description of the content, quality, condition or other characteristics of data.	AS/NZS ISO 19115.1:2015.	No Difference		
Definition					
Chapter 1 Reference	<i>Minimum en-route altitude (MEA).</i> The altitude for an en-route segment that provides adequate reception of relevant navigation facilities and ATS communications, complies with the airspace structure and provides the required obstacle clearance.	AIPNZ GEN 2.2.	No Difference		
Definition					
Chapter 1 Reference Definition	<i>Minimum obstacle clearance altitude (MOCA).</i> The minimum altitude for a defined segment of flight that provides the required obstacle clearance.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	





	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference	<i>Movement area.</i> That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, consisting of the manoeuvring area and the apron	CAR Part 1.	No Difference			
Definition						

Sixteenth edition 2018



	Report on entire Annex Annex 15, Amendment 43						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 1 Reference	<i>Navigation specification.</i> A set of aircraft and flight crew requirements needed to support performance-based navigation operations within a defined airspace. There are two kinds of navigation specifications:	AIPNZ GEN 2.2.	No Difference				
Definition	 Required navigation performance (RNP) specification. A navigation specification based on area navigation that includes the requirement for performance monitoring and alerting, designated by the prefix RNP, e.g. RNP 4, RNP APCH. Area navigation (RNAV) specification. A navigation specification based on area navigation that does not include the requirement for performance monitoring and alerting, designated by the prefix RNAV, e.g. RNAV 5, RNAV 1. Note 1.— The Performance-based Navigation (PBN) Manual (Doc 9613), Volume II, contains detailed guidance on navigation specifications. Note 2.— The term RNP, previously defined as "a statement of the navigation performance necessary for operation within a defined airspace", has been removed from this Annex as the concept of RNP has been overtaken by the concept of PBN. The term RNP in this Annex is now solely used in the context of navigation specifications that require performance monitoring and alerting, e.g. RNP 4 refers to the aircraft and operating requirements, including a 4 NM lateral performance with on-board performance monitoring and alerting that are detailed in Doc 9613. 						



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	<i>Next intended user.</i> The entity that receives the aeronautical data or information from the aeronautical information service.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference Definition	NOTAM. A notice distributed by means of telecommunication containing information concerning the establishment, condition or change in any aeronautical facility, service, procedure or hazard, the timely knowledge of which is essential to personnel concerned with flight operations.	CAR Part 1.	No Difference			
Chapter 1 Reference Definition	 Obstacle. All fixed (whether temporary or permanent) and mobile objects, or parts thereof, that: a) are located on an area intended for the surface movement of aircraft; or b) extend above a defined surface intended to protect aircraft in flight; or c) stand outside those defined surfaces and that have been assessed as being a hazard to air navigation. 	For a) and b), AC139-6, 1.3; for c) CAR Part 77, Appendix B, B.1.	No Difference			
Chapter 1 Reference Definition	<i>Obstacle/terrain data collection surface.</i> A defined surface intended for the purpose of collecting obstacle/terrain data.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		

Sixteenth edition 2018



	Zealand Annex 15, Amendment 4 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	Origination (aeronautical data or aeronautical information). The creation of the value associated with new data or information or the modification of the value of existing data or information.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference Definition	Originator (aeronautical data or aeronautical information). An entity that is accountable for data or information origination and/or from which the AIS organization receives aeronautical data and aeronautical information.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference Definition	<i>Orthometric height.</i> Height of a point related to the geoid, generally presented as an MSL elevation.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference Definition	Performance-based communication (PBC). Communication based on performance specifications applied to the provision of air traffic services. Note.— A required communication performance (RCP) specification includes communication performance requirements that are allocated to system components in terms of the communication to be provided and associated transaction time, continuity, availability, integrity, safety and functionality needed for the proposed operation in the context of a particular airspace concept.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.		

Sixteenth edition 2018



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference	Performance-based navigation (PBN). Area navigation based on performance requirements for aircraft operating along an ATS route, on an instrument approach procedure or in a designated airspace.	AIPNZ GEN 2.2.	No Difference			
Definition	Note.— Performance requirements are expressed in navigation specifications (RNAV specification, RNP specification) in terms of accuracy, integrity, continuity, availability and functionality needed for the proposed operation in the context of a particular airspace concept.					
Chapter 1 Reference Definition	 Performance-based surveillance (PBS). Surveillance based on performance specifications applied to the provision of air traffic services. Note.— A required surveillance performance (RSP) specification includes surveillance performance requirements that are allocated to system components in terms of the surveillance to be provided and associated data delivery time, continuity, availability, integrity, accuracy of the surveillance data, safety and functionality needed for the proposed operation in the context of a particular airspace concept. 	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.		
Chapter 1 Reference	<i>Portrayal.</i> Presentation of information to humans (ISO 19117*).	AS/NZS ISO 19117:2013.	No Difference			
Definition						




Annex 15, Amendment 43 Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	Position (geographical). Set of coordinates (latitude and longitude) referenced to the mathematical reference ellipsoid which define the position of a point on the surface of the Earth.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	Common usage term.	
Chapter 1 Reference Definition	<i>Post spacing.</i> Angular or linear distance between two adjacent elevation points.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.		
Chapter 1 Reference Definition	 Precision. The smallest difference that can be reliably distinguished by a measurement process. Note.— In reference to geodetic surveys, precision is a degree of refinement in performance of an operation or a degree of perfection in the instruments and methods used when taking measurements. 	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	Common usage term.	
Chapter 1 Reference	<i>Pre-flight information bulletin (PIB).</i> A presentation of current NOTAM information of operational significance, prepared prior to flight.	AIPNZ GEN 3.1, 3.4.1.	No Difference			
Definition						

Sixteenth edition 2018




Report on entire Annex 15, Amendment 43						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference	Prohibited area. An airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is prohibited.		Not Applicable		Term not used in New Zealand.	
Definition						
Chapter 1 Reference Definition	Quality. Degree to which a set of inherent characteristics fulfils requirements (ISO 9000*). Note 1.— The term "quality" can be used with adjectives such as poor, good or excellent. Note 2.— "Inherent", as opposed to "assigned", means existing in something, especially as a permanent characteristic.	AS/NZS ISO 9000:2016.	No Difference			
Chapter 1 Reference	<i>Quality assurance.</i> Part of quality management focused on providing confidence that quality requirements will be fulfilled (ISO 9000*).	AS/NZS ISO 9000:2016.	No Difference			
Definition						
Chapter 1 Reference	<i>Quality control.</i> Part of quality management focused on fulfilling quality requirements (ISO 9000*).	AS/NZS ISO 9000:2016.	No Difference			
Definition						





New Zealand	Annex 15, Amendment 43						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 1 Reference	<i>Quality management.</i> Coordinated activities to direct and control an organization with regard to quality (ISO 9000*).	AS/NZS ISO 9000:2016.	No Difference				
Definition							
Chapter 1 Reference	<i>Radio navigation service.</i> A service providing guidance information or position data for the efficient and safe operation of aircraft supported by one or more radio navigation aids.	CAR Part 1.	No Difference		Note: under "Aeronautical telecommunication service".		
Definition							
Chapter 1 Reference Definition	Required communication performance (RCP) specification. A set of requirements for air traffic service provision and associated ground equipment, aircraft capability, and operations needed to support performance-based communication.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.			
Chapter 1 Reference Definition	<i>Required surveillance performance (RSP) specification.</i> A set of requirements for air traffic service provision and associated ground equipment, aircraft capability, and operations needed to support performance-based surveillance.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.			





	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	 <i>Requirement.</i> Need or expectation that is stated, generally implied or obligatory (ISO 9000*). Note 1.— "Generally implied" means that it is custom or common practice for the organization, its customers and other interested parties, that the need or expectation under consideration is implied. Note 2.— A qualifier can be used to denote a specific type of requirement, e.g. product requirement, quality management requirement, customer requirement. Note 3.— A specified requirement is one which is stated, for example, in a document. Note 4.— Requirements can be generated by different interested parties. 	AS/NZS ISO 9000:2016.	No Difference			
Chapter 1 Reference Definition	Restricted area. An airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is restricted in accordance with certain specified conditions.	CAR 71.153.	No Difference			
Chapter 1 Reference Definition	<i>Route stage.</i> A route or portion of a route flown without an intermediate landing.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.		



ew Zealand Annex 15, Amendment 43						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 1 Reference Definition	SNOWTAM. A special series NOTAM given in a standard format providing a surface condition report notifying the presence or cessation of hazardous conditions due to snow, ice, slush, frost, standing water or water associated with snow, slush, ice or frost on the movement area.	CAR	No Difference	NIL	NIL	
Chapter 1 Reference Definition	<i>Station declination.</i> An alignment variation between the zero degree radial of a VOR and true north, determined at the time the VOR station is calibrated.		Not Applicable		"Station declination" does not appear in any SARPs.	
Chapter 1 Reference Definition	<i>Terrain.</i> The surface of the Earth containing naturally occurring features such as mountains, hills, ridges, valleys, bodies of water, permanent ice and snow, and excluding obstacles.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined in CARs.	Common usage term.	
Chapter 1 Reference Definition	 <i>Traceability.</i> Ability to trace the history, application or location of that which is under consideration (ISO 9000*). <i>Note.</i>— <i>When considering product, traceability can relate to:</i> — the origin of materials and parts; — the processing history; and — the distribution and location of the product after delivery. 	AS/NZS ISO 9000:2016.	No Difference			



	Annex 15, Amendment Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 1 Reference Definition	<i>Validation.</i> Confirmation, through the provision of objective evidence, that the requirements for a specific intended use or application have been fulfilled (ISO 9000*).	AS/NZS ISO 9000:2016.	No Difference				
Chapter 1 Reference Definition	Verification. Confirmation, through the provision of objective evidence, that specified requirements have been fulfilled (ISO 9000*). Note.— The term "verified" is used to designate the corresponding status.	AS/NZS ISO 9000:2016.	No Difference				
Chapter 1 Reference Definition	 VOLMET. Meteorological information for aircraft in flight. Data link-VOLMET (D-VOLMET). Provision of current aerodrome routine meteorological reports (METAR) and aerodrome special meteorological reports (SPECI), aerodrome forecasts (TAF), SIGMET, special air-reports not covered by a SIGMET and, where available, AIRMET via data link. VOLMET broadcast. Provision, as appropriate, of current METAR, SPECI, TAF and SIGMET by means of continuous and repetitive voice broadcasts. 	AIPNZ GEN 3.5, 7.	No Difference				



	Annex 15, Amendment 43 Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 1 Reference 1.2.1.1	1.2 Common reference systems for air navigation	AIPNZ GEN 2.1. 3.	No Difference				
ötandard	1.2.1 Horizontal reference system 1.2.1.1 The World Geodetic System — 1984 (WGS-84) shall be used as the horizontal (geodetic) reference system for international air navigation. Consequently, published aeronautical geographical coordinates (indicating latitude and longitude) shall be expressed in terms of the WGS-84 geodetic reference datum.						
	Note.— Comprehensive guidance material concerning WGS-84 is contained in the World Geodetic System — 1984 (WGS-84) Manual (Doc 9674).						

Sixteenth edition 2018




	Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 1 Reference 1.2.1.2 Recommendation	1.2.1.2 Recommendation. — In precise geodetic applications and some air navigation applications, temporal changes in the tectonic plate motion and tidal effects on the Earth's crust should be modelled and estimated. To reflect the temporal effect, an epoch should be included with any set of absolute station coordinates. Note 1.— The latest version of the WGS-84 (G2139) reference frame is realized through coordinates of 17 GPS tracking stations which are part of the GPS Control Segment. They are aligned to IGb14 (considered to be equivalent to International Terrestrial Reference Frame 2014 (ITRF 2014)) at epoch 2005.0. Note 2.— Another precise worldwide terrestrial coordinate system is the International Earth Rotation Service (IERS) Terrestrial Reference System (ITRS), and the realization of ITRS is the IERS ITRF. Guidance material regarding the ITRS is provided in Appendix C of Doc 9674. WGS-84 (G2139) is consistent with ITRF 2014 and in practical realization the difference between these two systems is statistically insignificant for most applications, meaning WGS-84 (G2139) and ITRF 2014 are essentially identical.	CARs.	Less protective or partially implemented or not implemented	Not specified in CARs.			

Sixteenth edition 2018




	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference 1.2.2.1 Standard	 1.2.2 Vertical reference system 1.2.2.1 Mean sea level (MSL) datum shall be used as the vertical reference system for international air navigation. Note 1.— The geoid globally most closely approximates MSL. It is defined as the equipotential surface in the gravity field of the Earth which coincides with the undisturbed MSL extended continuously through the continents. Note 2.— Gravity-related heights (elevations) are also referred to as orthometric heights while distances of points above the ellipsoid are referred to as ellipsoidal heights. 	CAR Part 1 definitions: Altitude and Elevation.	No Difference		
Chapter 1 Reference 1.2.2.2 Standard	1.2.2.2 The Earth Gravitational Model — 1996 (EGM-96) shall be used as the global gravity model for international air navigation.	CARs.	Less protective or partially implemented or not implemented	Not specified in CARs.	





	Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference 1.2.2.3 Standard	1.2.2.3 At those geographical positions where the accuracy of EGM-96 does not meet the accuracy requirements for elevation and geoid undulation on the basis of EGM-96 data, regional, national or local geoid models containing high resolution (short wavelength) gravity field data shall be developed and used. When a geoid model other than the EGM-96 model is used, a description of the model used, including the parameters required for height transformation between the model and EGM-96, shall be provided in the Aeronautical Information Publication (AIP). Note.— Specifications concerning determination and reporting (accuracy of field work and data integrity) of elevation and geoid undulation at specific positions at aerodromes/heliports are given in the PANS-AIM (Doc 10066), Appendix 1.	CARs.	Less protective or partially implemented or not implemented	Not specified in CARs.	





	Annex 15, Amendment 43						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 1 Reference 1.2.3.1 Standard	 1.2.3 Temporal reference system 1.2.3.1 The Gregorian calendar and Coordinated Universal Time (UTC) shall be used as the temporal reference system for international air navigation. Note 1.— A value in the time domain is a temporal position measured relative to a temporal reference system. Note 2.— UTC is a time scale maintained by the Bureau International de l'Heure and the IERS and forms the basis of a coordinated dissemination of standard frequencies and time signals. Note 3.— Guidance material relating to UTC is contained in Attachment D of Annex 5 — Units of Measurement to be Used in Air and Ground Operations. Note 4.— ISO Standard 8601* specifies the use of the Gregorian calendar and 24-hour local or UTC for information interchange while ISO Standard 19108* prescribes the Gregorian calendar and UTC as the primary temporal reference system for use with geographic information. 	CAR 172.101; AS/NZS ISO 19108:2003.	No Difference				

Sixteenth edition 2018



New Zealand	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference 1.2.3.2 Standard	1.2.3.2 When a different temporal reference system is used for some applications, the feature catalogue, or the metadata associated with an application schema or a data set, as appropriate, shall include either a description of that system or a citation for a document that describes that temporal reference system. <i>Note.</i> — <i>ISO Standard 19108*, Annex D, describes some aspects of calendars that may have to be considered in such a description.</i>		Not Applicable		
Chapter 1 Reference 1.3.1 Standard	1.3 Miscellaneous specifications 1.3.1 Aeronautical information products intended for international distribution shall include English text for those parts expressed in plain language. 	CAR 175.61(b)(8).	No Difference		
Chapter 1 Reference 1.3.2 Standard	1.3.2 Place names shall be spelt in conformity with local usage, transliterated, when necessary, into the ISO-Basic Latin alphabet.	CAR 175.61(b)(9).	No Difference		
Chapter 1 Reference 1.3.3 Recommendation	1.3.3 Recommendation. — Units of measurement used in the origination, processing and distribution of aeronautical data and aeronautical information should be consistent with the decision taken by the State in respect of the use of the tables contained in Annex 5.	CAR 175.61(b)(10).	No Difference		Note: the rule refers to rule 19.3, which incorporates Annex 5 by reference.


Sixteenth edition 2018



	Report on entire Annex							
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference			
Chapter 1 Reference 1.3.4	1.3.4 ICAO abbreviations shall be used in aeronautical information products whenever they are appropriate and their use will facilitate distribution of aeronautical data and aeronautical information.	AIPNZ GEN 2.2, 1.1.1.	No Difference					
Standard	 ISO Standard 8601 — Data elements and interchange formats — Information interchange — Representation of dates and times 9000 — Quality Management Systems — Fundamentals and Vocabulary 19101 — Geographic information — Reference model 19104 — Geographic information — Terminology 19108 — Geographic information — Temporal schema 19109 — Geographic information — Rules for application schema 19110 — Geographic information — Feature cataloguing schema 19115 — Geographic information — Metadata 19117 — Geographic information — Portrayal 19131 — Geographic information — Data product specification 							




	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.1	CHAPTER 2. RESPONSIBILITIES AND FUNCTIONS	Civil Aviation (CA) Act 1990 s72B(2)(g).	No Difference		
Standard					
	2.1 State responsibilities				
	2.1.1 Each Contracting State shall:				
	a) provide an aeronautical information service (AIS); or				
	 b) agree with one or more other Contracting State(s) for the provision of a joint service; or 				
	c) delegate the authority for the provision of the service to a non-governmental agency, provided the Standards and Recommended Practices of this Annex are adequately met.				
Chapter 2	2.1.2 Each Contracting State shall ensure that the	CA Act 1990 s72B(g);	No Difference		
Reference 2.1.2	provision of aeronautical data and aeronautical information covers its own territory and those areas over the high seas for which it is responsible for the provision of air traffic services (ATS).	CA Act 1990 \$72B(g); CAR Part 175.	no Difference		
Standard					





	R	eport on entire Annex			, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.3 Standard	2.1.3 The State concerned shall remain responsible for the aeronautical data and aeronautical information provided in accordance with 2.1.2. Aeronautical data and aeronautical information provided for and on behalf of a State shall clearly indicate that they are provided under the authority of that State, irrespective of the format in which they are provided.	CAR 175.61(b)(4).	No Difference		
Chapter 2 Reference 2.1.4 Standard	2.1.4 Each Contracting State shall ensure that the aeronautical data and aeronautical information provided are of required quality in accordance with 3.2.	CAR 175.59(b).	No Difference		
Chapter 2 Reference 2.1.5 Standard	2.1.5 Each Contracting State shall ensure that formal arrangements are established between originators of aeronautical data and aeronautical information and the AIS in relation to the timely and complete provision of aeronautical data and aeronautical information. Note.— The scope of aeronautical data and aeronautical information that would be the subject of formal arrangements is specified in Chapter 4.	CAR 175.59.	No Difference		





New Zealand	R	eport on entire Annex		Annex 13	5, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.2.1 Standard	 2.2 AIS responsibilities and functions 2.2.1 An AIS shall ensure that aeronautical data and aeronautical information necessary for the safety, regularity and efficiency of air navigation are made available in a form suitable for the operational requirements of the air traffic management (ATM) community, including: a) those involved in flight operations, including flight crews, flight planning and flight simulators; and b) the ATS unit responsible for flight information service and the services responsible for pre-flight information. Note.— A description of the ATM community is contained in the Global Air Traffic Management Operational Concept (Doc 9854). 	CAR 175.61(b)(2).	No Difference		
Chapter 2 Reference 2.2.2 Standard	2.2.2 An AIS shall receive, collate or assemble, edit, format, publish/store and distribute aeronautical data and aeronautical information concerning the entire territory of the State as well as those areas over the high seas for which the State is responsible for the provision of ATS. Aeronautical data and aeronautical information shall be provided as aeronautical information products. <i>Note.— An AIS may include origination functions.</i>	AIPNZ GEN 3.1, 2.	No Difference		Note: Aeropath provides the AIP service and the NOTAM service throughout the New Zealnd FIR (NZZC) and the Auckland Oceanic FIR (NZZO), except in the Cook, McMurdo, Samoa, and Tonga sectors, and Norfolk Island.

Sixteenth edition 2018 Annex 15, Amendment 43



R	eport on entire Annex			, Amendment 43
AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
2.2.3 Where 24-hour service is not provided, service shall be available during the whole period an aircraft is in flight in the area of responsibility of the AIS, plus a period of at least two hours before and after such a period. Service shall also be available at such other time as may be requested by an appropriate ground organization.		Not Applicable		24-hour service.
2.2.4 An AIS shall, in addition, obtain aeronautical data and aeronautical information to enable it to provide pre-flight information service and to meet the need for in-flight information:a) from the AIS of other States; and	CAR 175.59(b).	No Difference		
b) from other sources that may be available. Note.— One such source is the subject of a provision in 5.6.				
2.2.5 Aeronautical data and aeronautical information obtained under 2.2.4 a) shall, when distributed, be clearly identified as having the authority of the originating State.	CAR 175.61(b)(4).	No Difference		
2.2.6 Aeronautical data and aeronautical information obtained under 2.2.4 b) shall, if possible, be verified before distribution and if not verified shall, when distributed, be clearly identified as such.	CAR 175.61(b)(5).	No Difference		
	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice 2.2.3 Where 24-hour service is not provided, service shall be available during the whole period an aircraft is in flight in the area of responsibility of the AIS, plus a period of at least two hours before and after such a period. Service shall also be available at such other time as may be requested by an appropriate ground organization. 2.2.4 An AIS shall, in addition, obtain aeronautical data and aeronautical information to enable it to provide pre-flight information service and to meet the need for in-flight information: a) from the AIS of other States; and b) from other sources that may be available. <i>Note.</i> — One such source is the subject of a provision in 5.6. 2.2.5 Aeronautical data and aeronautical information obtained under 2.2.4 a) shall, when distributed, be clearly identified as having the authority of the originating State.	Standard or Recommended Practice Regulation or Document Reference 2.2.3 Where 24-hour service is not provided, service shall be available during the whole period an aircraft is in flight in the area of responsibility of the AIS, plus a period of at least two hours before and after such a period. Service shall also be available at such other time as may be requested by an appropriate ground organization. CAR 175.59(b). 2.2.4 An AIS shall, in addition, obtain aeronautical data and aeronautical information to enable it to provide pre-flight information: CAR 175.59(b). a) from the AIS of other States; and b) from other sources that may be available. <i>Note.</i> One such source is the subject of a provision in 5.6. CAR 175.61(b)(4). 2.2.5 Aeronautical data and aeronautical information obtained under 2.2.4 a) shall, when distributed, be clearly identified as having the authority of the originating State. CAR 175.61(b)(4). 2.2.6 Aeronautical data and aeronautical information obtained under 2.2.4 b) shall, if possible, be verified before distribution and if not verified shall, when distributed, be CAR 175.61(b)(5).	AERONAUTICAL INFORMATION SERVICES State Legislation, Regulation or Document Reference Level of implementation of SARP's 2.2.3 Where 24-hour service is not provided, service shall be available during the whole period an aircraft is in flight in the area of responsibility of the AIS, plus a period of at least two hours before and after such a period. Service shall also be available at such other time as may be requested by an appropriate ground organization. Not Applicable 2.2.4 An AIS shall, in addition, obtain aeronautical data and aeronautical information to enable it to provide pre-flight information: CAR 175.59(b). No Difference a) from the AIS of other States; and b) from other sources that may be available. Note.— One such source is the subject of a provision in 5.6. CAR 175.61(b)(4). No Difference 2.2.5 Aeronautical data and aeronautical information obtained under 2.2.4 a) shall, when distributed, be clearly identified as having the authority of the originating State. CAR 175.61(b)(4). No Difference 2.2.6 Aeronautical data and aeronautical information obtained under 2.2.4 b) shall, if possible, be verified before distribution and if not verified shall, when distributed, be CAR 175.61(b)(5). No Difference	AERONAUTICALINFORMATION SERVICES Standard or Recommended Practice State Legislation, Regulation or Document Reference Level of implementation of SARP's Text of the difference to be notified to ICAO 2.2.3 Where 24-hour service is not provided, service shall be available during the whole period an aircraft is in flight in the area of responsibility of the AIS, plus a period of at least two hours before and after such a period. Service shall also be available at such other time as may be requested by an appropriate ground organization. Not Applicable 2.2.4 An AIS shall, in addition, obtain acronautical data and aeronautical information to enable it to provide pre-flight information: a) from the AIS of other States; and b) from other sources that may be available. <i>Note.</i> — One such source is the subject of a provision in 5.6. CAR 175.59(b). No Difference 2.2.5 Aeronautical data and aeronautical information obtained under 2.2.4 a) shall, when distributed, be clearly identified as having the authority of the originating State. CAR 175.61(b)(4). No Difference 2.2.6 Aeronautical data and aeronautical information obtained under 2.2.4 b) shall, if possible, be verified before obtained under 2.2.4 b) shall, if possible, be verified before CAR 175.61(b)(5). No Difference


Sixteenth edition 2018



	R	eport on entire Annex			, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.2.7 Standard	2.2.7 An AIS shall promptly make available to the AIS of other States any aeronautical data and aeronautical information necessary for the safety, regularity or efficiency of air navigation required by them, to enable them to comply with 2.2.1.	CAR 175.61(b)(12).	No Difference		
Chapter 2 Reference 2.3.1 Standard	 2.3 Exchange of aeronautical data and aeronautical information 2.3.1 Each Contracting State shall designate the office to which all elements of aeronautical information products provided by other States shall be addressed. Such an office shall be qualified to deal with requests for aeronautical data and aeronautical information provided by other States. 	CAR 175.103(b)(1).	No Difference		
Chapter 2 Reference 2.3.2 Recommendation	2.3.2 Recommendation. — Formal arrangements should be established between those parties providing aeronautical data and aeronautical information on behalf of the States and their users in relation to the provision of the service. Note.— Guidance material on such formal arrangements is contained in the Aeronautical Information Services Manual (Doc 8126).	CAR 175.59.	No Difference		



	R	eport on entire Annex			, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.3 Standard	2.3.3 Where more than one international NOTAM office is designated within a State, the extent of responsibility and the territory covered by each office shall be defined.		Not Applicable		One only.
Chapter 2 Reference 2.3.4 Standard	2.3.4 An AIS shall arrange, as necessary, to satisfy operational requirements for the issuance and receipt of NOTAM distributed by telecommunication.	CAR 175.105(4)(iii).	No Difference		
Chapter 2 Reference 2.3.5 Standard	2.3.5 Wherever practicable, direct contact between AIS shall be established in order to facilitate the international exchange of aeronautical data and aeronautical information.	CAR 175.103(b)(1).	No Difference		






	R	eport on entire Annex	<u>.</u>	Annex 15	Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.6 Standard	 2.3.6 Except as provided in 2.3.8, one copy of each of the following aeronautical information products (where available) that have been requested by the AIS of a Contracting State shall be made available by the originating State and provided in the mutually agreed form(s), without charge, even where authority for publication/storage and distribution has been delegated to a non-governmental agency: a) Aeronautical Information Publication (AIP), including Amendments and Supplements; b) Aeronautical Information Circulars (AIC); c) NOTAM; and d) aeronautical charts. 	AIPNZ GEN 3.1, 3.	No Difference		
Chapter 2 Reference 2.3.7 Recommendation	2.3.7 Recommendation. — The exchange of more than one copy of the elements of aeronautical information products, and other air navigation documents, including those containing air navigation legislation and regulations, should be subject to bilateral agreement between the participating Contracting States and entities.		Not Applicable		
Chapter 2 Reference 2.3.8 Standard	2.3.8 When aeronautical data and aeronautical information are provided in the form of digital data sets to be used by the AIS, they shall be provided on the basis of agreement between the Contracting States concerned. <i>Note.</i> — <i>The intention is that States are able to access data for the purposes specified in 2.2.4.</i>	CAR 175.59.	No Difference		

Sixteenth edition 2018




New Zealand	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.9 Recommendation	2.3.9 Recommendation. — The procurement of aeronautical data and aeronautical information, including the elements of aeronautical information products, and other air navigation documents, including those containing air navigation legislation and regulations, by States other than Contracting States and by other entities should be subject to separate agreement between the participating States and entities.		Not Applicable		
Chapter 2 Reference 2.3.10 Standard	2.3.10 Globally interoperable aeronautical data and aeronautical information exchange models shall be used for the provision of data sets. Note 1.— Specifications concerning globally interoperable aeronautical data and aeronautical information exchange models are contained in the Procedures for Air Navigation Services — Aeronautical Information Management (PANS-AIM, Doc 10066). Note 2.— Guidance material on globally interoperable aeronautical data and aeronautical information exchange models is contained in Doc 8126.	CAR 175.59.	No Difference		





	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.1 Standard	 2.4 Copyright Note.— In order to protect the investment in the products of a State's AIS as well as to ensure better control of their use, States may wish to apply copyright to those products in accordance with their national laws. 2.4.1 Any aeronautical information product which has been granted copyright protection by the originating State and provided to another State in accordance with 2.3 shall only be made available to a third party on the condition that the third party is made aware that the product is copyright protected and provided that it is appropriately annotated that the product is subject to copyright by the originating State. 	AIPNZ GEN 0.1, 1.3.	No Difference		
Chapter 2 Reference 2.4.2 Standard	2.4.2 When aeronautical data and aeronautical information are provided to a State in accordance with 2.3.8, the receiving State shall not provide the digital data sets of the providing State to any third party without the consent of the providing State.	CAR 179.59.	Less protective or partially implemented or not implemented	Not specified in detail in the rule.	





Standard or Recommended Practice Regulation or Document Reference implementation of SARP's notified to ICAO reason for the difference Chapter 2 Leference 2.5 Cost recovery Civil Aviation (Aeronautical Information service) Levies Order No Difference 5.1 Recommendation.— The overhead cost of collecting and compiling aeronautical data and aeronautical information Service) Levies Order No Difference		R	eport on entire Annex		 , Amendment 43
Leference Civil Aviation No Difference 5.1 Recommendation.— The overhead cost of collecting and compiling aeronautical data and aeronautical information should be included in the cost basis for airport and air navigation services charges, as appropriate, in accordance with the principles contained in ICAO's Policies on Charges for Airports and Air Navigation Services (Doc 9082). 2001. Note.— When costs of collection and compilation of aeronautical data and aeronautical information are recovered through airport and air navigation services charges, the charge to an individual customer for the supply of a particular aeronautical information product may be based on the costs of printing paper copies, production of Note.— When costs of printing paper copies, production of	Annex Reference		Regulation or Document	implementation	Comments including the reason for the difference
S.1 Recommendation.— The overhead cost of collecting and compiling aeronautical data and aeronautical information should be included in the cost basis for airport and air navigation services charges, as appropriate, in accordance with the principles contained in ICAO's Policies on Charges for Airports and Air Navigation Services (Doc 9082). Service) Levies Order Note.— When costs of collection and compilation of aeronautical data and aeronautical information are recovered through airport and air navigation services charge to an individual customer for the supply of a particular aeronautical information product may be based on the costs of printing paper copies, production of Service) Levies Order	Chapter 2	2.5 Cost recovery	Civil Aviation	No Difference	
Recommendation.The overhead cost of collecting and compiling aeronautical data and aeronautical information should be included in the cost basis for airport and air navigation services charges, as appropriate, in accordance with the principles contained in ICAO's Policies on Charges for Airports and Air Navigation Services (Doc 9082).2001.Note.When costs of collection and compilation of aeronautical data and aeronautical information are recovered through airport and air navigation services charges, the charge to an individual customer for the supply of a particular aeronautical information product may be based on the costs of printing paper copies, production of2001.	Reference				
should be included in the cost basis for airport and air navigation services charges, as appropriate, in accordance with the principles contained in ICAO's Policies on Charges for Airports and Air Navigation Services (Doc 9082). Note.— When costs of collection and compilation of aeronautical data and aeronautical information are recovered through airport and air navigation services charges, the charge to an individual customer for the supply of a particular aeronautical information product may be based on the costs of printing paper copies, production of	.5.1		,		
	Recommendation	should be included in the cost basis for airport and air navigation services charges, as appropriate, in accordance with the principles contained in ICAO's Policies on Charges for Airports and Air Navigation Services (Doc 9082). Note.— When costs of collection and compilation of aeronautical data and aeronautical information are recovered through airport and air navigation services charges, the charge to an individual customer for the supply of a particular aeronautical information product may be based on the costs of printing paper copies, production of			



	R	Report on entire Annex Annex 15, Amendme				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 3 Reference 3.1	CHAPTER 3. AERONAUTICAL INFORMATION MANAGEMENT	CAR Part 175.	No Difference			
Standard	3.1 Information management requirements The information management resources and processes established by an aeronautical information service (AIS) shall be adequate to ensure the timely collection, processing, storing, integration, exchange and delivery of quality-assured aeronautical data and aeronautical information within the air traffic management (ATM) system.					



	R	eport on entire Annex			, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.2.1 Standard	3.2 Data quality requirements 3.2.1 Data accuracy The order of accuracy for aeronautical data shall be in accordance with its intended use. Note.— Specifications concerning the order of accuracy (including confidence level) for aeronautical data are contained in the Procedures for Air Navigation Services — Aeronautical Information Management (PANS-AIM, Doc 10066), Appendix 1.	CAR 175.61(b)(2)	No Difference		
Chapter 3 Reference 3.2.2 Standard	3.2.2 Data resolution The order of resolution of aeronautical data shall be commensurate with the actual data accuracy. Note 1.— Specifications concerning the resolution of aeronautical data are contained in the PANS-AIM (Doc 10066), Appendix 1. Note 2.— The resolution of the data contained in the database may be the same or finer than the publication resolution.	CAR 175.61(b)(1) and (2).	No Difference		

Sixteenth edition 2018





	Annex 15, Amendment 43					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 3 Reference 3.2.3.1 Standard	3.2.3 Data integrity 3.2.3.1 The integrity of aeronautical data shall be maintained throughout the data chain from origination to distribution to the next intended user. Note.— Specifications concerning the integrity classification related to aeronautical data are contained in the PANS-AIM (Doc 10066), Appendix 1.	CAR 175.61(b)(1) and (2).	No Difference			

Sixteenth edition 2018



	Annex 15, Amendment Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 3 Reference 3.2.3.2 Standard	 3.2.3.2 Based on the applicable integrity classification, procedures shall be put in place in order to: a) for routine data: avoid corruption throughout the processing of the data; b) for essential data: ensure corruption does not occur at any stage of the data processing life cycle (such as collection, processing, storing, integration, exchange and delivery) and include additional measures or steps as needed to address potential risks in the overall processing of aeronautical data to further ensure data integrity at this level; and c) for critical data: ensure corruption does not occur at any stage of the data processing life cycle (such as collection, processing, storing, integration, exchange and delivery) and include additional data to further ensure data integrity at this level; and c) for critical data: ensure corruption does not occur at any stage of the data processing life cycle (such as collection, processing, storing, integration, exchange and delivery) and include additional data integrity assurance processes to mitigate the risk of errors. Note.— Guidance concerning measures to ensure data integrity is contained in the Aeronautical Information Service Manual (Doc 8126), Part II, 4.1 and 6.2. 	CAR 175.61(b)(1) and (2).	No Difference			
Chapter 3 Reference 3.2.4 Standard	3.2.4 Data traceability Traceability of aeronautical data shall be ensured and retained as long as the data is in use.	CAR 175.65.	No Difference			

Sixteenth edition 2018





Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 3 Reference 3.2.5 Standard	3.2.5 Data timeliness Timeliness of aeronautical data shall be ensured by including limits on the effective period of the data elements. Note 1.— These limits may be associated with individual data elements or data sets. Note 2.— If the effective period is defined for a data set, it will account for the effective dates of all of the individual data elements.	CAR175.61(c).	No Difference			
Chapter 3 Reference 3.2.6 Standard	3.2.6 Data completeness Completeness of aeronautical data shall be ensured in order to support its intended use.	CAR 175.61(b)(1).	No Difference			
Chapter 3 Reference 3.2.7 Standard	3.2.7 Data format The format of delivered aeronautical data shall be adequate to ensure that the data is interpreted in a manner that is consistent with its intended use.	CAR 175.61(b)(2)(i).	No Difference			



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 3 Reference 3.3.1 Standard	 3.3 Aeronautical data and aeronautical information verification and validation 3.3.1 Aeronautical data and aeronautical information to be published as part of an aeronautical information product shall be checked before being submitted to the AIS in order to ensure that all necessary information has been included and that it is correct. 	CAR 175.59(b)(4), 175.61(b)(1).	No Difference			
Chapter 3 Reference 3.3.2 Standard	3.3.2 An AIS shall establish verification and validation procedures which ensure that upon receipt of aeronautical data and aeronautical information, quality requirements are met.	CAR 175.61.	No Difference			
Chapter 3 Reference 3.4.1 Standard	3.4 Data error detection 3.4.1 Digital data error detection techniques shall be used during the transmission and/or storage of aeronautical data and digital data sets.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.		
Chapter 3 Reference 3.4.2 Standard	3.4.2 Digital data error detection techniques shall be used in order to maintain the integrity levels as specified in 3.2.3. Note.— Detailed specifications concerning digital data error detection techniques are contained in the PANS-AIM (Doc 10066).	CARs.	Less protective or partially implemented or not implemented	Not specified.		



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 3 Reference 3.5.1 Standard	3.5 Use of automation 3.5.1 Automation shall be applied in order to ensure the quality, efficiency and cost-effectiveness of aeronautical information services. Note.— Guidance material on the development of databases and the establishment of data exchange services is contained in Doc 8126.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.		
Chapter 3 Reference 3.5.2 Standard	3.5.2 Due consideration to the integrity of data and information shall be given when automated processes are implemented and mitigating steps taken where risks are identified. Note.— Risks of altering the integrity of data and information may be introduced by automated processes in cases of unexpected systems behaviours.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.		
Chapter 3 Reference 3.5.3 Standard	 3.5.3 In order to meet the data quality requirements, automation shall: a) enable digital aeronautical data exchange between the parties involved in the data processing chain; and b) use aeronautical information exchange models and data exchange models designed to be globally interoperable. 	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.		

Sixteenth edition 2018

Annex 15, Amendment 43



Report on entire Annex

	Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 3 Reference 3.6.1 Standard	3.6 Quality management system 3.6.1 Quality management systems shall be implemented and maintained encompassing all functions of an AIS, as outlined in 2.2. The execution of such quality management systems shall be made demonstrable for each function stage. <i>Note.</i> — <i>Guidance material is contained in the</i> Manual on the Quality Management System for Aeronautical Information Services (<i>Doc 9839</i>).	CAR 175.67.	No Difference		The rule mandates a safety management system. which supersedes the requirement for a quality management system. Aeropath manages quality assurance in accordance with its Corporate Policy and Process Manual using ISO 9000 principles.		
Chapter 3 Reference 3.6.2 Recommendation	3.6.2 Recommendation. — Quality management should be applicable to the whole aeronautical data chain from data origination to distribution to the next intended user, taking into consideration the intended use of data.	CAR 175.67.	No Difference		See 3.6.1.		
Chapter 3 Reference 3.6.3 Recommendation	3.6.3 Recommendation. — The quality management system established in accordance with 3.6.1 should follow the ISO 9000 series of quality assurance standards and be certified by an accredited certification body.	CAR 175.67.	No Difference		See 3.6.1.		



Sixteenth edition 2018 Annex 15, Amendment 43



	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 3 Reference 3.6.4 Standard	3.6.4 Within the context of the established quality management system, the competencies and the associated knowledge, skills and attitudes required for each function shall be identified, and personnel assigned to perform those functions shall be appropriately trained. Processes shall be in place to ensure that personnel possess the competencies required to perform specific assigned functions. Appropriate records shall be maintained so that the qualifications of personnel can be confirmed. Initial and periodic assessments shall be established that require personnel to demonstrate the required competencies. Periodic assessments of personnel shall be used as a means to detect and correct shortfalls in knowledge, skills and attitudes.	CAR 175.67, AC00-3	No Difference		See 3.6.1.	
Chapter 3 Reference 3.6.5	3.6.5 Recommendation. — The training methodology established in accordance with 3.6.4 should follow the competency-based training and assessment (CBTA) methodology.	CAR 175, AC1001	No Difference			
Recommendation	Note 1.— Provisions related to the CBTA methodology are contained in the Procedures for Air Navigation Services — Training (PANS-TRG, Doc 9868) and in the Procedures for Air Navigation Services — Aeronautical Information Management (PANS-AIM, Doc 10066). Note 2.— Additional guidance concerning a CBTA methodology to ensure the competency of personnel in accordance with the Procedures for Air Navigation Services — Training (PANS-TRG, Doc 9868) is contained in the Manual on Aeronautical Information Services Training (Doc 9991).					




Sixteenth edition 2018 Annex 15, Amendment 43



	Annex 15, Amendment 43					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 3 Reference 3.6.6 Standard	3.6.6 Each quality management system shall include the necessary policies, processes and procedures, including those for the use of metadata, to ensure and verify that aeronautical data is traceable throughout the aeronautical information data chain so as to allow any data anomalies or errors detected in use to be identified by root cause, corrected and communicated to affected users.	CAR 175.67.	No Difference		See 3.6.1.	
Chapter 3 Reference 3.6.7 Standard	3.6.7 The established quality management system shall provide users with the necessary assurance and confidence that distributed aeronautical data and aeronautical information satisfy the aeronautical data quality requirements.	CAR 175.67.	No Difference		See 3.6.1.	
Chapter 3 Reference 3.6.8 Standard	3.6.8 All necessary measures shall be taken to monitor compliance with the quality management system in place.	CAR 175.67.	No Difference		See 3.6.1.	
Chapter 3 Reference 3.6.9 Standard	3.6.9 Demonstration of compliance of the quality management system applied shall be by audit. If nonconformity is identified, initiating action to correct its cause shall be determined and taken without undue delay. All audit observations and remedial actions shall be evidenced and properly documented.	CAR 175.67; Airways Quality Manual.	No Difference			




New Zealand	Annex 15, Amendment 43 Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 3 Reference 3.7.1 Standard	3.7 Human factors considerations 3.7.1 The organization of an AIS as well as the design, contents, processing and distribution of aeronautical data and aeronautical information shall take into consideration human factors principles which facilitate their optimum utilization.	CARs.	Less protective or partially implemented or not implemented	Not specified in CARs.			
Chapter 3 Reference 3.7.2 Standard	3.7.2 Due consideration shall be given to the integrity of information where human interaction is required and mitigating steps taken where risks are identified. <i>Note.</i> — <i>This may be accomplished through the design of systems, operating procedures or improvements in the operating environment.</i>	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.	Standard practice, despite not being specified.		





	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 4 Reference 4.1.1 Standard	CHAPTER 4. SCOPE OF AERONAUTICAL DATA AND AERONAUTICAL INFORMATION	CAR 175.61; 175.151 and 175.153.	No Difference			
	Note.— The scope of aeronautical data and aeronautical information provides the minimum requirement to support aeronautical information products and services, aeronautical navigation data bases, air navigation applications and air traffic management (ATM) systems.					
	4.1 Scope of aeronautical data and aeronautical information					
	4.1.1 The aeronautical data and aeronautical information to be received and managed by the aeronautical information service (AIS) shall include at least the following sub-domains:					
	a) national regulations, rules and procedures;b) aerodromes and heliports;					
	c) airspace;					
	 d) air traffic services (ATS) routes; a) instrument flight group during; 					
	e) instrument flight procedures;f) radio navigation aids/systems;					





New Zealand	Annex 15, Amendment 43 Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
	 g) obstacles; h) terrain; and i) geographic information. Note 1.— Detailed specifications concerning the content of each sub-domain are contained in the Procedures for Air Navigation Services — Aeronautical Information Management (PANS-AIM, Doc 10066), Appendix 1. Note 2.— Aeronautical data and aeronautical information in each sub-domain may be originated by more than one organization or authority. 					
Chapter 4 Reference 4.1.2 Standard	4.1.2 Determination and reporting of aeronautical data shall be in accordance with the accuracy and integrity classification required to meet the needs of the end-user of aeronautical data. Note.— Specifications concerning the accuracy and integrity classification related to aeronautical data are contained in the PANS-AIM (Doc 10066), Appendix 1.	CAR 175.61.	No Difference			
Chapter 4 Reference 4.2.1 Standard	4.2 Metadata4.2.1 Metadata shall be collected for aeronautical data processes and exchange points.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.		

Sixteenth edition 2018



	Annex 15, Amendment 43					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 4 Reference 4.2.2 Standard	4.2.2 Metadata collection shall be applied throughout the aeronautical information data chain, from origination to distribution to the next intended user. <i>Note.</i> — <i>Detailed specifications concerning metadata are</i> <i>contained in the PANS-AIM (Doc 10066).</i>	CARs.	Less protective or partially implemented or not implemented	Not specified.		
Chapter 5 Reference 5.1.1	CHAPTER 5. AERONAUTICAL INFORMATION PRODUCTS AND SERVICES	CAR 175.61.	No Difference			
Standard						
	5.1 General					
	5.1.1 Aeronautical information shall be provided in the form of aeronautical information products and associated services.					
	Note.— Specifications concerning the order of resolution of aeronautical data provided for each aeronautical information product are contained in the Procedures for Air Navigation Services — Aeronautical Information Management (PANS-AIM, Doc 10066), Appendix 1.					



	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.2 Standard	5.1.2 When aeronautical data and aeronautical information are provided in multiple formats, processes shall be implemented to ensure data and information consistency between formats.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.2.1 Standard	5.2 Aeronautical information in a standardized presentation 5.2.1 Aeronautical information provided in a standardized presentation shall include the aeronautical information publication (AIP), AIP Amendments, AIP Supplements, AIC, NOTAM and aeronautical charts. Note 1.— Detailed specifications about AIP, AIP Amendments, AIP Supplements, AIC and NOTAM are contained in the PANS-AIM (Doc 10066). Note 2.— Cases where digital data sets may replace the corresponding elements of the standardized presentation are detailed in the PANS-AIM (Doc 10066).	CAR 175.61.	No Difference		
Chapter 5 Reference 5.2.1.1 Standard	5.2.1.1 The AIP, AIP Amendment, AIP Supplement and AIC shall be provided on paper and/or as an electronic document.	CAR 175.61(13); AIPNZ GEN 0.1, 3.1.2 and 3.1.3.	No Difference		



Sixteenth edition 2018 Annex 15, Amendment 43



	Report on entire Annex Annex 15, Amendment 43				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.2	5.2.1.2 Recommendation .— The AIP, AIP Amendment, AIP Supplement and AIC when provided as an electronic document (eAIP) should allow for both displaying on electronic devices and printing on paper.	CAR 175.61(13); AIPNZ GEN 0.1, 3.1.2 and 3.1.3.	No Difference		Note: AIPNZ available in pdf on http://www.aip.net.nz/.
Recommendation					

Sixteenth edition 2018 Annex 15, Amendment 43



Report on entire Annex

		ort on entire Annex			*4m - 3
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2 Standard	 5.2.2 Aeronautical Information Publication Note 1.— The AIP is intended primarily to satisfy international requirements for the exchange of aeronautical information of a lasting character essential to air navigation. Note 2.— The AIP constitutes the basic information source for permanent information and long duration temporary changes. AIP shall include: a) a statement of the competent authority responsible for the air navigation facilities, services or procedures covered by the AIP; b) the general conditions under which the services or facilities are available for international use; c) a list of significant differences between the national regulations and practices of the State and the related ICAO Standards, Recommended Practices and Procedures, given in a form that would enable a user to differentiate readily between the requirements of the State and the related ICAO Standards, Recommended Practices and Procedures, given in a form that would enable a user to differentiate readily between the requirements of the State and the related ICAO Standards, Recommended Practices and Procedures, given in a form that would enable a user to differentiate readily between the requirements of the State and the related ICAO provisions; d) the choice made by a State in each significant case where an alternative course of action is provided for ICAO Standards, Recommended Practices and Procedures. 	a) CAR 175.151(c)(1); AIPNZ GEN 3; b) CAR 175.151(c)(2); AIPNZ GEN 3; c) CAR 175.151(c)(3); AIPNZ GEN 1.7; d) CAR 175.151(c)(4); AIPNZ GEN 1.7.	No Difference		AIPNZ GEN 1.7 contains a link to the CAANZ web site at http://www.caa.govt.nz/ica o/icao-compliance/, on which a full compliance checklist for each Annex (except 9 and 17) is published.

Sixteenth edition 2018



Report on entire Annex 15, Amen					, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3 Standard	5.2.3 AIP Supplement A checklist of valid AIP Supplements shall be regularly provided. Note.— Detailed specifications concerning the frequency for providing checklists of valid AIP Supplements are contained in the PANS-AIM (Doc 10066).	CAR 175.157(c).	No Difference		A new set of AIP Supplements is issued in booklet form each AIRAC cycle. Checklist is contents page. Cancelled Supplements are listed on the last page.
Chapter 5 Reference 5.2.4.1 Standard	 5.2.4 Aeronautical Information Circulars 5.2.4.1 An AIC shall be used to provide: a) a long-term forecast of any major change in legislation, regulations, procedures or facilities; or b) information of a purely explanatory or advisory nature liable to affect flight safety; or c) information or notification of an explanatory or advisory nature concerning technical, legislative or purely administrative matters. 	CAR 175.201; AC175-1 Appendix 2.	No Difference		
Chapter 5 Reference 5.2.4.2 Standard	5.2.4.2 An AIC shall not be used for information that qualifies for inclusion in AIP and NOTAM.	AC175-1 Appendix 2.	No Difference		



New Zealand	Annex 15, Amendment 43 Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.3 Standard	5.2.4.3 The validity of AIC currently in force shall be reviewed at least once a year.	CAR 175.201(d).	No Difference		
Chapter 5 Reference 5.2.4.4 Standard	5.2.4.4 A checklist of currently valid AIC shall be regularly provided. Note.— Detailed specifications concerning the frequency for providing checklists of valid AIC are contained in the PANS-AIM (Doc 10066).	CAR 175.201(d).	No Difference		

Sixteenth edition 2018

Annex 15, Amendment 43



Report on entire Annex

	Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 5	5.2.5 Aeronautical charts	AIPNZ GEN 3.2, 4.	No Difference		Note: d) not applicable.		
Reference							
5.2.5.1	<i>Note.</i> — Annex 4 — Aeronautical Charts provides Standards and Recommended Practices including provision requirements for each chart type.						
Standard							
	5.2.5.1 The aeronautical charts listed below shall, when available for designated international aerodromes/heliports, form part of the AIP, or be provided separately to recipients of the AIP:						
	a) Aerodrome/Heliport Chart — ICAO;						
	b) Aerodrome Ground Movement Chart — ICAO;						
	c) Aerodrome Obstacle Chart — ICAO Type A;						
	d) Aerodrome Obstacle Chart — ICAO Type B (when available);						
	e) Aerodrome Terrain and Obstacle Chart — ICAO (Electronic);						
	f) Aircraft Parking/Docking Chart — ICAO;						
	g) Area Chart — ICAO;						
	h) ATC Surveillance Minimum Altitude Chart — ICAO;						
	i) Instrument Approach Chart — ICAO;						
	j) Precision Approach Terrain Chart — ICAO;						
	k) Standard Arrival Chart — Instrument (STAR) — ICAO;						
		1			1		



	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	Standard or Recommended Practice				
	l) Standard Departure Chart — Instrument (SID) — ICAO; and				
	m) Visual Approach Chart — ICAO.				
Chapter 5 Reference 5.2.5.2	5.2.5.2 The En-route Chart — ICAO shall, when available, form part of the AIP, or be provided separately to recipients of the AIP.	AIPNZ GEN 3.2, 4.2.	No Difference		Four Enroute Charts and three Area Charts produced.
Standard					
Chapter 5 Reference 5.2.5.3	5.2.5.3 The aeronautical charts listed below shall, when available, be provided as aeronautical information products:a) World Aeronautical Chart — ICAO 1:1 000 000;	AIPNZ GEN 3.2, 4.2.	No Difference		Two 1:1 000 000; six 1:500 000s; 14 1:250 000; and two 1:125 000 charts are produced. Item d) is not applicable.
Standard	 b) Aeronautical Chart — ICAO 1:500 000; c) Aeronautical Navigation Chart — ICAO Small Scale; and d) Plotting Chart — ICAO chart. 				
Chapter 5 Reference 5.2.5.4	5.2.5.4 Recommendation. — Electronic aeronautical charts should be provided based on digital databases and the use of geographic information systems.		Not Applicable		E-charts not yet published.
Recommendation					

Sixteenth edition 2018

Annex 15, Amendment 43



	R	eport on entire Annex			Willing , and
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.5 Standard	5.2.5.5 The chart resolution of aeronautical data shall be that as specified for a particular chart. Note.— Specifications concerning the chart resolution for aeronautical data are contained in the PANS-AIM (Doc 10066), Appendix 1.	CAR 175.103(b)(4).	Different in character or other means of compliance	The rule requires conformance to the "applicable standards for the charts" which implies those of Annex 4.	
Chapter 5 Reference 5.2.6 Standard	5.2.6 NOTAM Note.— Detailed specifications for NOTAM, including formats for SNOWTAM and ASHTAM, are contained in the PANS-AIM (Doc 10066). A checklist of valid NOTAM shall be regularly provided. Note.— Detailed specifications concerning the frequency for providing checklists of valid NOTAM are contained in the PANS-AIM (Doc 10066).	CAR 175.105(6).	No Difference		Note; SNOWTAM and ASHTAM formats are not used in New Zealand.

Sixteenth edition 2018



	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.1.1 Standard	 5.3 Digital data sets 5.3.1 General 5.3.1.1 Digital data shall be in the form of the following data sets: a) AIP data set; b) terrain data sets; c) obstacle data sets; d) aerodrome mapping data sets; and e) instrument flight procedure data sets. Note.— Detailed specifications concerning the content of the digital data sets are contained in the PANS-AIM (Doc 10066). 	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.1.2 Standard	5.3.1.2 Each data set shall be provided to the next intended user together with at least the minimum set of metadata that ensures traceability. <i>Note.</i> — <i>Detailed specifications concerning metadata are contained in the PANS-AIM (Doc 10066).</i>	CARs.	Less protective or partially implemented or not implemented	Not specified.	



Sixteenth edition 2018 Annex 15, Amendment 43



	Annex 15, Amendment 43 Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.1.3 Standard	5.3.1.3 A checklist of valid data sets shall be regularly provided.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.2.1 Recommendation	5.3.2 AIP data set 5.3.2.1 Recommendation. — An AIP data set should be provided covering the extent of information as provided in the AIP.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.2.2 Recommendation	5.3.2.2 Recommendation. — When it is not possible to provide a complete AIP data set, the data subset(s) that are available should be provided.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.2.3 Standard	5.3.2.3 The AIP data set shall contain the digital representation of aeronautical information of lasting character (permanent information and long duration temporary changes) essential to air navigation.	CARs.	Less protective or partially implemented or not implemented	Not specified.	

Sixteenth edition 2018



New Zealand	R	eport on entire Annex		Annex 15	5, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.3.1 Standard	 5.3.3 Terrain and obstacle data sets Note 1.— Numerical requirements for terrain and obstacle data sets are contained in the PANS AIM (Doc 10066), Appendices 1 and 8. Note 2.— Requirements for terrain and obstacle data collection surfaces are contained in the PANS-AIM (Doc 10066), Appendix 8. 5.3.3.1 The coverage areas for terrain and obstacle data sets shall be specified as: Area 1: the entire territory of a State; Area 2: within the vicinity of an aerodrome, subdivided as follows: Area 2a: a rectangular area around a runway that comprises the runway strip plus any clearway that exists; Note.— See Annex 14, Volume I, Chapter 3, for dimensions for runway strips. Area 2b: an area extending from the ends of Area 2a in the direction of departure, with a length of 10 km and a splay of 15 per cent to each side; Area 2c: an area extending outside Area 2a and Area 2b at a distance of not more than 10 km from the boundary of Area 2a; and Area 2d: an area outside Areas 2a, 2b and 2c up 	CARs.	Less protective or partially implemented or not implemented	Not specified.	Note: digital terrain data is available from a number of commercial suppliers, including Land Information New Zealand, a State-Owned Enterprise (SOE).
	to a distance of 45 km from the aerodrome reference point, or to an existing terminal control area (TMA) boundary, whichever is nearest;				

Sixteenth edition 2018 Annex 15, Amendment 43



vew Zealallu	Report on entire Annex Annex 15, Amendment 43					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
	 Area 3: the area bordering an aerodrome movement area that extends horizontally from the edge of a runway to 90 m from the runway centre line and 50 m from the edge of all other parts of the aerodrome movement area; and Area 4: the area extending 900 m prior to the runway threshold and 60 m each side of the extended runway centre line in the direction of the approach on a precision approach runway, Category II or III. 					
Chapter 5 Reference 5.3.3.2 Recommendation	5.3.3.2 Recommendation. — Where the terrain at a distance greater than 900 m (3 000 ft) from the runway threshold is mountainous or otherwise significant, the length of Area 4 should be extended to a distance not exceeding 2 000 m (6 500 ft) from the runway threshold.		Not Applicable		See 5.3.3.	
Chapter 5 Reference 5.3.3.3.1 Standard	5.3.3.3 Terrain data sets 5.3.3.1 Terrain data sets shall contain the digital representation of the terrain surface in the form of continuous elevation values at all intersections (points) of a defined grid, referenced to common datum.		Not Applicable		See 5.3.3.	



Report on entire Annex 15, Amendment 43						
Annex Reference	AERONAUTICAL INFORMATION SERVICES State Legislation, Regulation or Document i			Text of the difference to be notified to ICAO	Comments including the reason for the difference	
	Standard or Recommended Practice	Reference	of SARP's			
Chapter 5	5.3.3.3.2 Terrain data shall be provided for Area 1.		Not Applicable		See 5.3.3.	
Reference						
5.3.3.3.2						
Standard						
Chapter 5	5.3.3.3.3 For aerodromes regularly used by international		Not Applicable		See 5.3.3.	
Reference	civil aviation, terrain data shall be provided for:					
5.3.3.3.3	a) Area 2a;					
Standard	b) the take-off flight path area; and					
	c) an area bounded by the lateral extent of the aerodrome obstacle limitation surfaces.					
Chapter 5	5.3.3.3.4 Recommendation. — For aerodromes regularly		Not Applicable		See 5.3.3.	
Reference	used by international civil aviation, additional terrain data					
5.3.3.3.4	should be provided within Area 2 as follows:					
Recommendation	a) in the area extending to a 10-km radius from the ARP; and					
	b) within the area between 10 km and the TMA boundary or a 45-km radius (whichever is smaller), where terrain penetrates a horizontal terrain data collection surface specified as 120 m above the lowest runway elevation.					

Sixteenth edition 2018 Annex 15, Amendment 43



New Zealallu	Annex 15, Amendment 43 Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 5 Reference 5.3.3.3.5 Recommendation	5.3.3.3.5 Recommendation. — Arrangements should be made for coordinating the provision of terrain data for adjacent aerodromes where their respective coverage areas overlap to assure that the data for the same terrain is correct.		Not Applicable		See 5.3.3.		
Chapter 5 Reference 5.3.3.3.6 Recommendation	5.3.3.3.6 Recommendation. — For those aerodromes located near territorial boundaries, arrangements should be made among States concerned to share terrain data.		Not Applicable				
Chapter 5 Reference 5.3.3.3.7 Recommendation	5.3.3.3.7 Recommendation. — For aerodromes regularly used by international civil aviation, terrain data should be provided for Area 3.		Not Applicable		See 5.3.3.		
Chapter 5 Reference 5.3.3.3.8 Standard	5.3.3.3.8 For aerodromes regularly used by international civil aviation, terrain data shall be provided for Area 4 for all runways where precision approach Category II or III operations have been established and where detailed terrain information is required by operators to enable them to assess the effect of terrain on decision height determination by use of radio altimeters.		Not Applicable		See 5.3.3.		

Sixteenth edition 2018



	Report on entire Annex Annex 15, Amendment 43						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 5 Reference 5.3.3.3.9 Recommendation	5.3.3.3.9 Recommendation. — Where additional terrain data is collected to meet other aeronautical requirements, the terrain data sets should be expanded to include this additional data.		Not Applicable		See 5.3.3.		
Chapter 5 Reference 5.3.3.4.1 Standard	5.3.3.4 Obstacle data sets 5.3.3.4.1 Obstacle data sets shall contain the digital representation of the vertical and horizontal extent of obstacles.		Not Applicable		See 5.3.3.		
Chapter 5 Reference 5.3.3.4.2 Standard	5.3.3.4.2 Obstacle data shall not be included in terrain data sets.		Not Applicable		See 5.3.3.		
Chapter 5 Reference 5.3.3.4.3 Standard	5.3.3.4.3 Obstacle data shall be provided for obstacles in Area 1 whose height is 100 m or higher above ground.		Not Applicable		See 5.3.3.		

Sixteenth edition 2018 Annex 15, Amendment 43



	Report on entire Annex Annex 15, Amendment 43					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 5 Reference 5.3.3.4.4 Standard	5.3.3.4.4 For aerodromes regularly used by international civil aviation, obstacle data shall be provided for all obstacles within Area 2 that are assessed as being a hazard to air navigation.		Not Applicable		See 5.3.3.	
Chapter 5 Reference 5.3.3.4.5 Standard	 5.3.3.4.5 For aerodromes regularly used by international civil aviation, obstacle data shall be provided for: a) Area 2a for those obstacles that penetrate an obstacle data collection surface outlined by a rectangular area around a runway that comprises the runway strip plus any clearway that exists. The Area 2a obstacle collection surface shall have a height of 3 m above the nearest runway elevation measured along the runway centre line, and for those portions related to a clearway, if one exists, at the elevation of the nearest runway end; b) objects in the take-off flight path area which project above a plane surface having a 1.2 per cent slope and having a common origin with the take-off flight path area; and c) penetrations of the aerodrome obstacle limitation surfaces. Note.— Take-off flight path areas are specified in Annex 4, 3.8.2. Aerodrome obstacle limitation surfaces are specified in Annex 14, Volume 1, Chapter 4. 		Not Applicable		See 5.3.3.	

Sixteenth edition 2018 Annex 15, Amendment 43



	Annex 15, Amendment 43 Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.3.4.6 Recommendation	 5.3.3.4.6 Recommendation.— For aerodromes regularly used by international civil aviation, obstacle data should be provided for Areas 2b, 2c and 2d for obstacles that penetrate the relevant obstacle data collection surface specified as follows: a) Area 2b: an area extending from the ends of Area 2a in the direction of departure, with a length of 10 km and a splay of 15 per cent to each side. The Area 2b obstacle collection surface has a 1.2 per cent slope extending from the ends of Area 2a and Area 2b at a distance of not more than 10 km from the boundary of Area 2a. The Area 2c obstacle collection surface has a 1.2 per cent slope extending outside Area 2a and Area 2b at a distance of not more than 10 km from the boundary of Area 2a. The Area 2c obstacle collection surface has a 1.2 per cent slope extending outside Area 2a and Area 2b at a distance of not more than 10 km from the boundary of Area 2c. bas the elevation of the row of Area 2a and Area 2b at a distance of not more than 10 km from the boundary of Area 2c and Area 2b at a distance of not more than 10 km from the boundary of Area 2a. The initial elevation of Area 2c has the elevation of the point of Area 2a at which it commences; and c) Area 2d: an area outside Areas 2a, 2b and 2c up to a distance of 45 km from the aerodrome reference point, or to an existing TMA boundary, whichever is nearest. The Area 2d obstacle collection surface has a height of 100 m above ground; except that data need not be collected for obstacles less than a height of 15 m above ground in Area 2c. 		Not Applicable		See 5.3.3.

Sixteenth edition 2018



	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.3.4.7 Recommendation	5.3.3.4.7 Recommendation. — Arrangements should be made for coordinating the provision of obstacle data for adjacent aerodromes where their respective coverage areas overlap to assure that the data for the same obstacle is correct.		Not Applicable		See 5.3.3.
Chapter 5 Reference 5.3.3.4.8 Recommendation	5.3.3.4.8 Recommendation. — For those aerodromes located near territorial boundaries, arrangements should be made among States concerned to share obstacle data.		Not Applicable		No New Zealand aerodromes in this category.
Chapter 5 Reference 5.3.3.4.9 Recommendation	5.3.3.4.9 Recommendation. — For aerodromes regularly used by international civil aviation, obstacle data should be provided for Area 3 for obstacles that penetrate the relevant obstacle data collection surface extending a half-metre (0.5 m) above the horizontal plane passing through the nearest point on the aerodrome movement area.		Not Applicable		See 5.3.3.
Chapter 5 Reference 5.3.3.4.10 Standard	5.3.3.4.10 For aerodromes regularly used by international civil aviation, obstacle data shall be provided for Area 4 for all runways where precision approach Category II or III operations have been established.		Not Applicable		See 5.3.3.
Chapter 5 Reference 5.3.3.4.11 Recommendation	5.3.3.4.11 Recommendation. — Where additional obstacle data is collected to meet other aeronautical requirements, the obstacle data sets should be expanded to include this additional data.		Not Applicable		See 5.3.3.

Sixteenth edition 2018 Annex 15, Amendment 43



	Report on entire Annex Annex 15, Amendment 43				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.4.1 Standard	5.3.4 Aerodrome mapping data sets 5.3.4.1 Aerodrome mapping data sets shall contain the digital representation of aerodrome features. Note.— Aerodrome features consist of attributes and geometries, which are characterized as points, lines or polygons. Examples include runway thresholds, taxiway guidance lines and parking stand areas.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.4.2 Recommendation	5.3.4.2 Recommendation. — Aerodrome mapping data sets should be made available for aerodromes regularly used by international civil aviation.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.5.1 Standard	5.3.5 Instrument flight procedure data sets 5.3.5.1 Instrument flight procedure data sets shall contain the digital representation of instrument flight procedures.	CARs.	Less protective or partially implemented or not implemented	Not specified.	

Sixteenth edition 2018



	Annex 15, Amene Report on entire Annex					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 5 Reference 5.3.5.2 Recommendation	5.3.5.2 Recommendation. — Instrument flight procedure data sets should be made available for aerodromes regularly used by international civil aviation.	CARs.	Less protective or partially implemented or not implemented	Not specified.		
Chapter 5 Reference 5.4.1.1	5.4 Distribution services	CAR 175,61(c).	No Difference			
Standard	5.4.1 General					
	5.4.1.1 Aeronautical information products shall be distributed to authorized users who request them.					
Chapter 5 Reference 5.4.1.2 Standard	5.4.1.2 AIP, AIP Amendments, AIP Supplements and AIC shall be made available by the most expeditious means.	AIPNZ GEN 3.1, 3.6	No Difference		Internet distribution via www.aip.net.nz is the most expeditious means; hard copy distributed by postal or courier services.	
Chapter 5 Reference 5.4.1.3	5.4.1.3 Recommendation. — Global communication networks such as the Internet should, whenever practicable, be employed for the provision of aeronautical information products.	AIPNZ GEN 0.1, 3.1.2.	No Difference		See www.aip.net.nz.	
Recommendation						



	Report on entire Annex 15, Amendment 43					
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 5 Reference 5.4.2.1 Standard	5.4.2 NOTAM distribution 5.4.2.1 NOTAM shall be distributed on the basis of a request.	CAR 175.253.	No Difference		Note: NOTAM are also available on https://www.ifis.airways.c o.nz/.	
Chapter 5 Reference 5.4.2.2 Standard	5.4.2.2 NOTAM shall be prepared in conformity with the relevant provisions of the ICAO communication procedures.	CAR 175.251.	No Difference			
Chapter 5 Reference 5.4.2.3 Standard	5.4.2.3 The aeronautical fixed service (AFS) shall, whenever practicable, be employed for NOTAM distribution.	CAR 175.253(d).	No Difference			
Chapter 5 Reference 5.4.2.4 Standard	5.4.2.4 When a NOTAM is sent by means other than the AFS, a six-digit date-time group indicating the date and time of NOTAM origination, and the identification of the originator shall be used, preceding the text. The originating State shall select the NOTAM that are to be given international distribution.	CAR 175.253(e).	No Difference			

Sixteenth edition 2018



	W Zealand Annex 15, Amendment 43 Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 5 Reference 5.4.2.5 Standard	5.4.2.5 International exchange of NOTAM shall take place only as mutually agreed between the international NOTAM offices concerned, and between the NOTAM offices and multinational NOTAM processing units.	CAR 175.253(c).	No Difference				
Chapter 5 Reference 5.4.2.6 Standard	5.4.2.6 The originating State shall, upon request, grant distribution of NOTAM series other than those distributed internationally.	CAR 175.253(a)(2).	No Difference		Note availability on https://www.ifis.airways.c o.nz/.		
Chapter 5 Reference 5.4.2.7 Recommendation	5.4.2.7 Recommendation. — Selective distribution lists should be used when practicable. Note.— Guidance material relating to selective distribution lists is contained in the Aeronautical Information Services Manual (Doc 8126).	CAR 175.253(f).	No Difference				

Sixteenth edition 2018




New Zealand	R	eport on entire Annex		Annex 15	, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.4.3.1 Recommendation	5.4.3 Data set information services 5.4.3.1 Recommendation.— When provided, the digital data sets specified in 5.3 should be made available through information services. Note 1.— In the context of system-wide information management, the notion of information service addresses machine-to-machine interaction in a service-oriented architecture. Note 2.— Procedures on information services are contained in the Procedures for Air Navigation Services — Information Management (PANS-IM, Doc 10199). Note 3.— Guidance material on information services can be found in the Manual on System-wide Information Management Implementation (Doc 10203).		Not Applicable		
Chapter 5 Reference 5.4.3.1.1 Standard	5.4.3.1.1 A data set information service shall provide, as a minimum, the ability to query and retrieve, as a whole, each of the digital data sets specified in 5.3.				

Sixteenth edition 2018



	Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 5 Reference 5.4.3.1.2 Recommendation	5.4.3.1.2 Recommendation. — A data set information service should provide the ability to query and retrieve selected elements of the digital data sets specified in 5.3. Note.— Guidance material on how to query digital data sets is contained in the Aeronautical Information Services Manual (Doc 8126), Part IV.						
Chapter 5 Reference 5.4.3.1.3 Recommendation	5.4.3.1.3 Recommendation. — A data set information service should provide the option to subscribe to notifications on data set updates.						
Chapter 5 Reference 5.5.1 Standard	5.5 Pre-flight information service 5.5.1 For any aerodrome/heliport used for international air operations, aeronautical information relative to the route stages originating at the aerodrome/heliport shall be made available to flight operations personnel, including flight crews and services responsible for pre-flight information.	CAR 175.61(b)(13) and 175.107.	No Difference				





	Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.5.2	5.5.2 Aeronautical information provided for pre-flight planning purposes shall include information of operational significance from the elements of aeronautical information products.	CAR 175.107(b).	No Difference		
Standard	Note 1.— The elements of aeronautical information products may be limited to national publications and when practicable, those of adjacent States, provided a complete library of aeronautical information is available at a central location and means of direct communications are available with that library. Note 2.— A recapitulation of valid NOTAM of operational significance and other information of urgent character may be made available to flight crews in the form of plain-language pre-flight information bulletins (PIB). Guidance material on the preparation of PIB is contained in Doc 8126.				
Chapter 5 Reference 5.6.1 Standard	5.6 Post-flight information service 5.6.1 For any aerodrome/heliport used for international air operations, arrangements shall be made to receive information concerning the state and operation of air navigation facilities or services noted by flight crews.	CAR 175.107(c), 175.107(d).	No Difference		


Sixteenth edition 2018



New Zealand Annex 15, Anne					, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.6.2 Standard	5.6.2 The arrangements specified in 5.6.1 shall ensure that such information is made available to the aeronautical information service (AIS) for distribution as the circumstances necessitate.	CAR 175.107(d).	No Difference		
Chapter 5 Reference 5.6.3 Standard	5.6.3 For any aerodrome/heliport used for international air operations, arrangements shall be made to receive information concerning the presence of wildlife hazards observed by flight crews.	AC12-1.	No Difference		Note: normal practice for flight crew is to notify ATS, who will forward the information as appropriate.
Chapter 5 Reference 5.6.4 Standard	5.6.4 The information about presence of wildlife hazards shall be made available to the aeronautical information service for distribution as the circumstances necessitate. Note.— See Annex 14, Volume I, Chapter 9, Section 9.4.	AC12-1.	No Difference		Note: normal practice for flight crew is to notify ATS, who will forward the information as appropriate. The aerodrome operator will normally initiate NOTAM action if they perceive a hazard.




	Annex 15, Amendment - Annex Annex 15, Amendment - Annex 15, Amendm				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.1	CHAPTER 6. AERONAUTICAL INFORMATION UPDATES	CAR 175.59(b)(3) and 175.153(a)(6).	No Difference		
Standard	6.1 General specifications Aeronautical data and aeronautical information shall be kept up to date.				





New Zealand	R	Report on entire Annex Annex Annex Annex 15, Amendment 43			
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.1	6.2 Aeronautical information regulation and control (AIRAC)	CAR 175.61(c).	No Difference		
Standard	 6.2.1 Information concerning the following circumstances shall be distributed under the regulated system (AIRAC), i.e. basing establishment, withdrawal or significant changes upon a series of common effective dates at intervals of 28 days, including 8 November 2018: a) limits (horizontal and vertical), regulations and in the second second				
	procedures applicable to:1) flight information regions;				
	2) control areas;				
	3) control zones;				
	4) advisory areas;				
	5) air traffic services (ATS) routes;				
	 permanent danger, prohibited and restricted areas (including type and periods of activity when known) and air defence identification zones (ADIZ); 				
	7) permanent areas or routes or portions thereof where the possibility of interception exists;				
	b) positions, frequencies, call signs, identifiers, known irregularities and maintenance periods of radio navigation aids, and communication and surveillance facilities;				
	c) holding and approach procedures, arrival and				



	Annex 15, Amendment 43 Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	 departure procedures, noise abatement procedures and any other pertinent ATS procedures; d) transition levels, transition altitudes and minimum sector altitudes; e) meteorological facilities (including broadcasts) and procedures; f) runways and stopways; g) taxiways and aprons; h) aerodrome ground operating procedures (including low visibility procedures); 				
	i) approach and runway lighting; andj) aerodrome operating minima if published by a State.				
Chapter 6 Reference 6.2.2 Standard	6.2.2 The information notified under the AIRAC system shall not be changed further for at least another 28 days after the effective date, unless the circumstance notified is of a temporary nature and would not persist for the full period.	CAR 175.61(c).	No Difference		

Sixteenth edition 2018



	R	eport on entire Annex		Annex 15, Amendment 43		
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
Chapter 6 Reference 6.2.3 Standard	6.2.3 Information provided under the AIRAC system shall be made available by the aeronautical information service (AIS) so as to reach recipients at least 28 days in advance of the effective date. Note.— AIRAC information is distributed by the AIS unit at least 42 days in advance of the AIRAC effective dates with the objective of reaching recipients at least 28 days in advance of the effective date.	CAR 175.61(c)(3).	No Difference			
Chapter 6 Reference 6.2.4 Standard	6.2.4 When information has not been submitted by the AIRAC date, a NIL notification shall be distributed not later than one cycle before the AIRAC effective date concerned.	CAR 175.61(c)(7).	No Difference			
Chapter 6 Reference 6.2.5 Standard	6.2.5 Implementation dates other than AIRAC effective dates shall not be used for pre-planned operationally significant changes requiring cartographic work and/or for updating of navigation databases.	CAR 175.61(c)(1).	No Difference			

Sixteenth edition 2018





	Annex 15, Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.6 Recommendation	6.2.6 Recommendation. — The regulated system (AIRAC) should be used for the provision of information relating to the establishment and withdrawal of, and premeditated significant changes in, the circumstances listed below: a) position, height and lighting of navigational	CAR 175.61(c).	No Difference		
	obstacles; b) hours of service of aerodromes, facilities and services; c) customs, immigration and health services; d) temporary danger, prohibited and restricted areas and navigational hazards, military exercises and mass movements of aircraft; and e) temporary areas or routes or portions thereof where the possibility of interception exists.				

Sixteenth edition 2018

Annex 15, Amendment 43



Report on entire Annex

	Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.7 Recommendation	 6.2.7 Recommendation.— Whenever major changes are planned and where advance notice is desirable and practicable, information should be made available by the AIS so as to reach recipients at least 56 days in advance of the effective date. This should be applied to the establishment of, and premeditated major changes in, the circumstances listed below, and other major changes if deemed necessary: a) new aerodromes for international instrument flight rules (IFR) operations; b) new runways for IFR operations at international aerodromes; c) design and structure of the ATS route network; d) design and structure of a set of terminal procedures (including change of procedure bearings due to magnetic variation change); e) circumstances listed in 6.2.1 if the entire State or any significant portion thereof is affected or if cross-border coordination is required. Note.— Guidance material on what constitutes a major change is included in the Aeronautical Information Services Manual (Doc 8126). 	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.	Note: information of this nature is normally promulgated by SUP or AIC at least 56 days in advance.



	R	Annex 15, Amendment 43			
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.1.1	6.3 Aeronautical information product updates	CAR 175.153(a)(6).	No Difference		
Standard	6.3.1 AIP updates 6.3.1.1 The aeronautical information publication (AIP) shall be amended or reissued at such regular intervals as may be necessary to keep it up to date.				
Chapter 6 Reference 6.3.1.2 Standard	6.3.1.2 Permanent changes to the AIP shall be published as AIP Amendments.	CAR 175.153(a)(6); AIPNZ GEN 3.1, 3.2.4.	No Difference		
Chapter 6 Reference 6.3.1.3 Standard	6.3.1.3 Temporary changes of long duration (three months or longer) and information of short duration which contains extensive text and/or graphics shall be published as AIP Supplements.	CAR 175.103(a)(3); AIPNZ GEN 3.1, 3.3.	No Difference		



	R	eport on entire Annex			, Amendment 43
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.2.1 Standard	6.3.2 NOTAM 6.3.2.1 When an AIP Amendment or an AIP Supplement is published in accordance with AIRAC procedures, a Trigger NOTAM shall be originated. <i>Note.— Detailed specifications concerning the Trigger</i> <i>NOTAM are contained in the</i> Procedures for Air Navigation Services — Aeronautical Information Management <i>(PANS-AIM, Doc 10066).</i>	CAR 175.61(c)(6).	No Difference		The NOTAM remains in force for 14 days.
Chapter 6 Reference 6.3.2.2 Standard	6.3.2.2 A NOTAM shall be originated and issued promptly whenever the information to be distributed is of a temporary nature and of short duration, or when operationally significant permanent changes or temporary changes of long duration are made at short notice, except for extensive text and/or graphics.	CAR 175.105(5).	No Difference		

Sixteenth edition 2018




New Zealand Annex Report on entire Annex					x 15, Amendment 43		
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference		
Chapter 6	6.3.2.3 A NOTAM shall be originated and issued	CAR 175.105(5); AC175-1	No Difference				
Reference	concerning the following information:	Appendix 3.					
6.3.2.3	 a) establishment, closure or significant changes in operation of aerodrome(s) or heliport(s) or runways; 						
Standard							
	 b) establishment, withdrawal or significant changes in operation of aeronautical services (aerodromes, AIS, ATS, communications, navigation and surveillance (CNS), meteorology (MET), search and rescue (SAR), etc.); 						
	c) establishment, withdrawal or significant changes in operational capability of radio navigation and air-ground communication services. This includes: interruption or return to operation, change of frequencies, change in notified hours of service, change of identification, change of orientation (directional aids), change of loca-tion, power increase or decrease amounting to 50 per cent or more, change in broadcast schedules or contents, or irregularity or unreliability of operation of any radio navigation and air-ground communication services or limitations of relay stations including operational impact, affected service, frequency and area;						
	 d) unavailability of back-up and secondary systems, having a direct operational impact; 						
	e) establishment, withdrawal or significant changes to visual aids;						
	f) interruption of or return to operation of major components of aerodrome lighting systems;						
	g) establishment, withdrawal or significant changes to procedures for air navigation services;						

Sixteenth edition 2018




New Zealand	Report on entire Annex Annex 15, Amendment 43				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	 h) occurrence or correction of major defects or impediments in the manoeuvring area; 				
	i) changes to and limitations on availability of fuel, oil and oxygen;				
	j) major changes to search and rescue facilities and services available;				
	 k) establishment, withdrawal or return to operation of hazard beacons marking obstacles to air navigation; 				
	 changes in regulations requiring immediate action, e.g. prohibited areas for SAR action; 				
	 m) presence of hazards not otherwise promulgated, which affect air navigation (including obstacles, military exercises and operations, intentional and unintentional radio frequency interferences, rocket launches, displays, fireworks, sky lanterns, rocket debris, races and major parachuting events); 				
	 n) conflict zones which affect air navigation (to include information that is as specific as possible regarding the nature and extent of threats of that conflict and its consequences for civil aviation); 				
	Note.— Guidance related to conflict zones is contained in the Risk Assessment Manual for Civil Aircraft Operations Over or Near Conflict Zones (Doc 10084).				
	 planned laser emissions, laser displays and search lights if pilots' night vision is likely to be impaired; 				
	p) erecting or removal of, or changes to, obstacles to air				






	Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	navigation in the take-off/climb, missed approact approact approach areas and runway strip;	1,			
	 q) establishment or discontinuance (includin activation or deactivation) as applicable, or change in the status of prohibited, restricted or danger areas; 	-			
	 r) establishment or discontinuance of areas or routes of portions thereof where the possibility of interception exists and where the maintenance of guard on the VHF emergency frequency 121.5 MHz is required; 	n			
	s) allocation, cancellation or change of location indicators;	n			
	 t) changes in aerodrome/heliport rescue and firefightin category provided (see Annex 14, Volume I, Chapte 9, and Attachment A, Section 17); 	-			
	 u) presence or removal of, or significant changes in hazardous conditions due to snow, slush, ic radioactive material, toxic chemicals, volcanic as deposition or water on the movement area; 	2,			
	 v) outbreaks of epidemics necessitating changes in notified requirements for inoculations and quarantin measures; 				
	 w) observations or forecasts of space weather phenomena, the date and time of their occurrence, the flight levels where provided and portions of the airspace which may be affected by the phenomena; 	e			
	 x) an operationally significant change in volcan activity, the location, date and time of volcan eruptions and/or horizontal and vertical extent of volcanic ash cloud, including direction of movement 	c f			





	R	Annex 15, Amendment 43			
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	flight levels and routes or portions of routes which could be affected;				
	 y) release into the atmosphere of radioactive materials or toxic chemicals following a nuclear or chemical incident, the location, date and time of the incident, the flight levels and routes or portions thereof which could be affected and the direction of movement; 				
	 z) establishment of operations of humanitarian relief missions, such as those undertaken under the auspices of the United Nations, together with procedures and/or limitations which affect air navigation; and 				
	 aa) implementation of short-term contingency measures in cases of disruption, or partial disruption, of ATS and related supporting services. 				
	Note.— See Annex 11, 2.31 and Attachment C to that Annex.				
	Note.— Specifications concerning the timely promulgation of information by NOTAM are contained in Chapter 6 of the Procedures for Air Navigation Services — Aeronautical Information Management (PANS-AIM, Doc 10066).				





	Annex 15, Amendment 43 Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.2.4 Standard	 6.3.2.4 The following information shall not be notified by NOTAM: a) routine maintenance work on aprons and taxiways which does not affect the safe movement of aircraft; b) runway marking work, when aircraft operations can safely be conducted on other available runways, or the equipment used can be removed when necessary; c) temporary obstructions in the vicinity of aerodromes/heliports that do not affect the safe operation of aircraft; d) partial failure of aerodrome/heliport lighting facilities where such failure does not directly affect aircraft operations; e) partial temporary failure of air-ground communications when suitable alternative frequencies are known to be available and are operative; f) the lack of apron marshalling services and road traffic control; g) the unserviceability of location, destination or other instruction signs on the aerodrome movement area; h) parachuting when in uncontrolled airspace under VFR (see 6.3.2.3 m)), when controlled, at promulgated sites or within danger or prohibited areas; i) training activities by ground units; j) unavailability of back-up and secondary systems if 	and 3.	No Difference		
	these do not have an operational impact;				


Sixteenth edition 2018



ew Zealand	Annex 15, Amendment 43 Report on entire Annex				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	 k) limitations to airport facilities or general services with no operational impact; 				
	l) national regulations not affecting general aviation;				
	m) announcement or warnings about possible/potential limitations, without any operational impact;				
	n) general reminders on already published information;				
	 o) availability of equipment for ground units without containing information on the operational impact for airspace and facility users; 				
	 p) information about laser emissions without any operational impact and fireworks below minimum flying heights; 				
	 q) closure of movement area parts in connection with planned work locally coordinated of duration of less than one hour; 				
	 r) closure or unavailability of, or changes in, operation of aerodrome(s)/heliport(s) outside the aerodrome(s)/heliport(s) operational hours; and 				
	s) other non-operational information of a similar temporary nature.				
	Note.— Information which relates to an aerodrome and its vicinity and does not affect its operational status may be distributed locally during pre-flight or in-flight briefing or other local contact with flight crews.				
	distributed locally during pre-flight or in-flight briefing or				



	Report on entire Annex 15, Amendment 43				
Annex Reference	AERONAUTICAL INFORMATION SERVICES Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.3.1 Standard	6.3.3 Data set updates 6.3.3.1 Data sets shall be amended or reissued at such regular intervals as may be necessary to keep them up to date.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 6 Reference 6.3.3.2 Standard	6.3.3.2 Permanent changes and temporary changes of long duration (three months or longer) made available as digital data shall be issued in the form of a complete data set or a subset that includes only the differences from the previously issued complete data set.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 6 Reference 6.3.3.3 Recommendation	6.3.3.3 Recommendation. — When made available as a completely reissued data set, the differences from the previously issued complete data set should be indicated.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 6 Reference 6.3.3.4 Recommendation	6.3.3.4 Recommendation. — When temporary changes of short duration are made available as digital data (digital NOTAM), they should use the same aeronautical information model as the complete data set.	CAR Part 175.	Less protective or partially implemented or not implemented	Not specified.	



Annex 15, Amendment 43



Report on entire Annex						
Annex Reference	AERONAUTICAL INFORMATION SERVICES	State Legislation, Regulation or Decument	Level of	Text of the difference to be notified to ICAO	Comments including the reason for the difference	
	Standard or Recommended Practice	Regulation or Document Reference	implementation of SARP's	nouned to ICAO	reason for the difference	
Chapter 6	6.3.3.5 Updates to AIP and digital data sets shall be	CAR Part 175.	Less protective	Not specified.		
Reference	synchronized.		or partially			
6.3.3.5			implemented or			
			not			
			implemented			
Standard						

- END -