Compass use

INSTRUMENT FLYING

Objective

To turn accurately onto and maintain compass headings, compensating for known errors in the magnetic compass.

Considerations

Variation

- Difference between true North and magnetic North
- · Bar magnet will align itself with lines of flux



Air exercise

- · Demonstration of acceleration and deceleration errors
- Demonstration of turning errors

Makina a turn

- Check present heading against desired heading use shortest arc
- Decide on amount of overturn or underturn ONUS
- · Lookout and roll in using rate one turn balance
- Anticipate roll out
- Select reference point
- Level wings hold for compass to settle
- Check heading and make correction if required (3° per second)

Deviation

- · Aircraft magnet acted on by things other than the lines of flux, ie, metal objects, aircraft, etc
- Compensated for by a compass swing done by an engineer

Dip

- At magnetic equator flux lines are parallel with surface
- As they approach the poles they dip down towards the earth's surface
- A bar magnet tries to align with the lines of flux dip towards the earth's surface
- To compensate, the bar magnet is set on a pivot, but some residual dip remains
- The pivot arrangement is fairly unstable, so compass card and magnets are immersed in fluid that damps out oscillations - also providing lubrication



Acceleration errors

SAND

· Apparent turn South when Accelerating, apparent turn North when Decelerating





Airmanship

- · Compass checked during taxi for correct sense and runway heading
- Turn coordinator checked for

· Compass system checked for

- serviceability before flight
- Deviation card is valid
- Keep metal items as far away from the compass as possible

Aeroplane management

• Suction gauge should be checked during engine run-up (4.5-5.2 inches)

Human factors

- Helpful to have a 3D picture of compass in your head
- In-flight mental calculations should be kept to a minimum
- · Cover failed instruments to avoid confusion

Civil Aviation Authority of New Zealand

• To compensate must Overturn on North

 Use rate one turn, maximum error on N or $S = 30^{\circ}$

Turning errors

ONUS

and Underturn on South

- Lookout

- serviceability